

PRODUCT-DETAILS

TY242MX

CABLE TIE 40LB 8IN UV BLACK NYLON



General Information

Extended Product Type	TY242MX
Product ID	7TAG009130R0004
EAN	5414363061984
Catalog Description	CABLE TIE 40LB 8IN UV BLACK NYLON
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 208mm (8.2 Inches), Width of 3.6mm (0.14 Inches), Thickness of 1mm (0.04 Inch), Tensile Strength Rating of 178 Newtons (40 Pounds), Bulk Pack

Ordering

E-Number (Finland)	1381518
EAN	5414363061984

Dimensions

Product Net Width	0.14 in 3.6 mm
Product Net Depth / Length	8.2 in 208 mm
Product Net Weight	.002 lb .907 g

Container Information

Package Level 1 Units	1000 piece
Package Level 1 Width	12 in 305 mm
Package Level 1 Depth / Length	18 in 457 mm
Package Level 2 Units	10000 piece
Package Level 2 Width	9.89 in 251 mm
Package Level 2 Height	13.7 in 348 mm
Package Level 2 Depth / Length	21 in 533 mm

Additional Information

Brand / Label	Ty-Rap
Bundle Diameter	0.08 to 2.01 in 2 to 51 mm
Color	Black
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Number of Batteries	0
Product Name	PLASTIC CABLE TIE
Product Type	High Performance
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Standards	UL E49405
Tensile Strength	40 lb 178 N
Thickness	0.04 in 1.0 mm
UPC	786210871035

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TY242MX
Instructions and Manuals	TY242MX

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

