



PRODUCT-DETAILS

TY272M

CABLE TIE 120LB 9IN NATURAL NYLON



General Information

Extended Product Type	TY272M
Product ID	7TAG009340R0002
EAN	5414363062967
Catalog Description	CABLE TIE 120LB 9IN NATURAL NYLON
Long Description	Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 222.3mm (8.75 Inches), Width of 6.99mm (0.275 Inches), Thickness of 1.78mm (0.07 Inches), Tensile Strength Rating of 534 Newtons (120 Pounds), Bulk Pack

Ordering

EAN	5414363062967
-----	---------------

Dimensions

Product Net Width	0.275 in 6.99 mm
Product Net Depth / Length	8.75 in 222.3 mm
Product Net Weight	.007 lb 3.175 g

Container Information

Package Level 1 Units	500 piece
Package Level 2 Units	5000 piece
Package Level 2 Width	13.4 in 340 mm
Package Level 2 Height	9.3 in 236 mm
Package Level 2 Depth / Length	20.9 in 531 mm

Additional Information

Brand / Label	Ty-Rap
Bundle Diameter	0.236 to 1.97 in 6 to 50 mm
Color	Natural
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Number of Batteries	0
Product Name	NYLON CABLE TIES AND ACCESSORIES
Product Type	High Performance
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Standards	UL E49405
Tensile Strength	120 lb 530 N
Thickness	0.07 in 1.78 mm
UPC	786210839899

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TY272M
Declaration of Conformity - CE	9AKK107492A9841
Instructions and Manuals	TY272M

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

