

PRODUCT-DETAILS

TY5253MX

CABLE TIE 50LB 11 UV BLK 2-PC DIST



General Information

Extended Product Type	TY5253MX
Product ID	7TAG009180R0007
EAN	5414363065593
Catalog Description	CABLE TIE 50LB 11 UV BLK 2-PC DIST
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (220 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/215 Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 289.7mm (11.40 Inches), Width of 4.82mm (0.19 Inches), Thickness of 1.41mm (0.055 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds)

Ordering

EAN	5414363065593
-----	---------------

Dimensions

Product Net Width	0.19 in 4.82 mm
Product Net Depth / Length	11.40 in 289.7 mm
Product Net Weight	.005 lb 2.268 g

Container Information

Package Level 1 Units	100 piece
Package Level 2 Units	500 piece
Package Level 2 Width	5.25 in 133 mm
Package Level 2 Height	5.5 in 140 mm
Package Level 2 Depth / Length	15.25 in 387 mm

Additional Information

Brand / Label	Ty-Rap
Bundle Diameter	0.138 to 3.07 in 3.5 to 78 mm
Color	Black
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Number of Batteries	0
Product Name	CABLE TIES
Product Type	High Performance
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Tensile Strength	50 lb 222 N
Thickness	0.055 in 1.4 mm
UPC	786210885131

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TY5253MX
Declaration of Conformity - CE	9AKK107492A9841
Instructions and Manuals	TY5253MX

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

