

PRODUCT-DETAILS

TY535M

CBL TIE 50LB 8IN NAT NYL MNTG HOLE



General Information

Extended Product Type	TY535M
Product ID	7TAG009520R0068
EAN	5414363066170
Catalog Description	CBL TIE 50LB 8IN NAT NYL MNTG HOLE
Long Description	Integrated Mounting Hole Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, Length of 198.88mm (7.83 Inches), Width of 4.83mm (0.19 Inches), Thickness of 1.4mm (0.055 Inches), Tensile Strength Rating of 222 Newtons (50 pounds), #10 Screw for Mounting

Ordering

E-Number (Finland)	1381525
EAN	5414363066170

Dimensions

Product Net Width	0.19 in 4.83 mm
Product Net Depth / Length	7.83 in 198.88 mm
Product Net Weight	.004 lb 1.814 g

Container Information

Package Level 1 Units	100 piece
Package Level 1 Width	6 in 152 mm
Package Level 1 Depth / Length	12.5 in 318 mm
Package Level 2 Units	500 piece
Package Level 2 Width	5.7 in 145 mm
Package Level 2 Height	6.6 in 168 mm
Package Level 2 Depth / Length	9.89 in 251 mm

Additional Information

Brand / Label	Ty-Rap
Bundle Diameter	0.138 to 1.77 in 3.5 to 45 mm
Color	Natural
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Number of Batteries	0
Product Name	NYLON CABLE TIES AND ACCESSORIES
Product Type	Integrated Mounting Hole
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Standards	UL E49405
Tensile Strength	50 lb 222 N
Thickness	0.055 in 1.4 mm
UPC	786210805153

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TY535M
Instructions and Manuals	TY535M

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5044 >> Mounted Head Ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

