



Tough Enough To Get The Job Done, Feels Great In Hand



Designed For HVAC/R Technicians

- Features the essential tests HVAC techs use everyday
- Built tough to last on day-to-day job sites
- Backed by 2-year limited warranty

We Made It Better!

- New UEi Look
- Adds over-molded rubber grip
- Adds wireless ability to App
- Adjustable NCV sensitivity
- Adds higher CAT safety rating
- Adds 2-Year Limited Warranty

All The Pro Features You Love

- Same essential professional HVAC/R tests as our popular DL579
- Plus the quality upgrades you've come to expect from UEi



Dual backlit display



Test lead storage



Magnetic strap



Easy access batteries

Wireless Capability

- Available at Google Play and The App Store, search **UEi HUB**
- Measure remotely, graph, log, save and send results



*Pricing is suggested trade net pricing and subject to change without notice. Confirm with local wholesaler.



— BACKED BY —
UEI
QUALITY

2
YEAR
WARRANTY



Safety Rated: CATIV 600V / CATIII 1000V
Certified by ETL to IEC 61010-1, 3rd edition



Includes

- Silicone Test Leads (ATL58)
- Alligator Clips (AAC3)
- Temperature Probes K-type (ATT29)
- Zippered Pouch (AC570)
- Batteries AAA (4)
- Certificate of Conformity

EPC Replaces Previous Model

- DL579



Made in KOREA

Clamp Meter Line Comparison



	DL599	DL589	EPC	DL569+
True RMS	YES	YES	YES	NO
Voltage AC/DC	1000 AC / 1000 DC	750 AC / 1000 DC	750 AC / 1000 DC	750 AC / 1000 DC
Amperage AC/DC	600 AC / 600 DC	600 AC / 600 DC	400 AC	400 AC
Capacitance	9999µF	2000µF	4000µF	4000µF
Resistance	60M	60M	40M	40M
Continuity & Diode Test	YES	YES	YES	YES
AC / DC microamps	2000µA (DC only)	2000µA	2000µA (DC only)	2000µA
Min/Max	YES	YES	YES	YES
Hold	YES	YES	YES	YES
Ranging	Auto/ Man	Auto/ Man	Auto/ Man	Man
Display count	6000	6000	4000	4000
Auto power off	YES	YES	YES	YES
Low battery warning	YES	YES	YES	YES
Test lead storage	YES	YES	YES	YES
Dual display	YES	YES	YES	YES
High voltage alert	YES	YES	YES	YES
Auto Calibration	YES	YES	YES	YES
Easy access battery latches	YES	YES	YES	YES
Temperature (K-type input)	-328 to 2462°F	-328 to 2462°F	-328 to 2462°F	
Frequency (Hertz)	YES	YES	YES	
Duty cycle	YES	YES	YES	
LRA inrush	YES	YES	YES	
Magnetic mount/strap	YES	YES	YES	
Wireless to app	YES	YES	YES	
NCV (LED & Audible)	YES	YES	YES	
Backlight	YES	YES	YES	
Low Z (impedance)	YES	YES	YES	
Worklight	YES	YES		
Temperature differential	YES	YES		
DC Zero	YES	YES		
POWER(W, VA, VAR)	YES			
Power Factor	YES			
Auto AC/DC selection for V/A	YES			
3-Phase motor rotation test	YES			
Motor unbalanced test	YES			
Low pass filter	YES			
Safety Rating	CAT IV 600V CAT III 1000V	CAT IV 600V CAT III 1000V	CAT IV 600V CAT III 1000V	CAT IV 600V CAT III 1000V
Warranty	2 YEAR	2 YEAR	2 YEAR	1 YEAR