

Refrigerant Leak Detector

Detects the latest refrigerants using a leak size indicator and 3 sensitivity levels



Functions

- Detects industry standard refrigerants including, but not limited to: HFC, R-134A, R-410A, R-404A, R-407C & R-507 (R-134A, R-410A sensitivity ≥ 0.05 oz/yr)
- Hydrocarbon Blends: HC-12a®, OZ-12a®

Features

- Solid electrolyte semiconductor sensor
- Digital numeric leak size indicator
- 3 Sensitivity levels
- Visual LED leak alarm
- Automatic calibration & ambient level reset
- Splash resistant
- Worklight
- 2-Year limited warranty



Includes



- Sensors filters 5 (RLDTF)
- Leak test vial (RLDLS)
- Batteries 4 (AA)
- Hard carrying case
- Manual

Specifications

Sensitivity	.05 oz/yr R134a .025 oz/yr R22, R1234yf
Sensor Life	> 300 Hours
Response Time	≤1sec
Power Supply	4 (AA) Alkaline
Battery Life	4 - 6 Hrs. Continuous
Warm-Up Time	<20 Seconds
Probe Length	17 inches
Numerical Display	7 Segment Digital (1-9)
Display Refresh Rate	3/sec.
Operating Temperature	-24 to 125°F (-31 to 52°C)
Operating Humidity	<95% non-condensing
Operating Altitude	<10,000 ft.
Storage Temperature	-4 to 122°F (20 to 50°C)
Pollution Degree	4
Weight, lbs	1.5 Lbs
Certifications	SAE J2791, SAE J2913 EN14624-2012 ASHRAE 173-2012
Warranty	2-Year limited warranty



WWW.UEITEST.COM

PORTLAND, OR
Headquarters & Recertification Center
1-800-547-5740 • info@ueitest.com

INDIANAPOLIS, IN
Recertification Center
1-800-547-5740 • info@ueitest.com

VANCOUVER, BC
Recertification Center
ISO/IEC 17025:2005 • NIST Certification
1-877-475-0648 • infocanada@ueitest.com