Shaded Pole Unit Bearing Fan Totally Enclosed



APPLICATIONS:

Designed for use on unit bearing fans.

FEATURES:

- Permanently lubricated bearings
- Individually boxed.
- Impedance protected
- Suitable For All Angle Operation
- 24" Cord with Molded Strain Relief
- Cast Iron Housing
- Includes vibration dampener hub washer, speed nut and four mounting screws (2 to 35 watt)





Clockwise Lead End Rotation

Watts	RPM	Voltage	Catalog Number	List	Amps	Rotation	Dia. A	Total B	Total C	Shaft Dia. x Length	Ship Wt. (lbs)	Industry Numbers
2.5	1550	115	2102	46	0.3	CWLE	3.6	3.4	3.8	1/4 x 20THD x 0.5	2	5111
4	1550	115	2115	49	0.3	CWLE	3.6	3.4	3.8	1/4 x 20THD x 0.5	3	5211
4	1550	230	2123	71	0.2	CWLE	3.6	3.4	3.8	1/4 x 20THD x 0.5	3	5221
5	1550	115	2119	67	0.6	CWLE	3.6	3.4	3.8	1/4 x 20THD x 0.5	2.53	PP7577M, D582
6	1550	115	2117	50	0.4	CWLE	3.6	3.8	4.3	1/4 x 20THD x 0.5	3.04	5311
9	1550	115	2108	51	0.6	CWLE	3.6	3.8	4.3	1/4 x 20THD x 0.5	3.1	5411
9	1550	230	2110	56	0.3	CWLE	3.6	3.8	4.3	1/4 x 20THD x 0.5	5	5421
16	1550	115	2112	71	1	CWLE	3.6	4.1	4.5	1/4 x 20THD x 0.5	3.9	5811
16	1550	230	2114	72	0.5	CWLE	3.6	4.1	4.5	1/4 x 20THD x 0.5	5	5821
25	1550	115	2125	158	1.1	CWLE	3.9	4	4.5	1/4 x 20THD x 0.5	5	ESPL25EM1
25	1550	230	2126	163	0.6	CWLE	3.9	4	4.5	1/4 x 20THD x 0.5	5	ESPL25EM2
35	1550	115	2129	158	1.4	CWLE	3.9	4	4.5	1/4 x 20THD x 0.5	4.58	ESPL35EM1
35	1550	230	2131	163	0.7	CWLE	3.9	4	4.5	1/4 x 20THD x 0.5	4.58	ESPL35EM2
50	1550	115	2133	176	1.7	CWLE	4	5.7	7.2	0.375 x 1.5	3	ESPOL50EM1
50	1550	230	2135	182	0.9	CWLE	4	7.7	9.2	0.375 x 1.5	6.28	ESPOL50EM2

Counterclockwise Lead End Rotation

Watts	RPM	Voltage	Catalog Number	List	Amps	Rotation	Dia. A	Total B	Total C	Shaft Dia. x Length	Ship Wt. (lbs)	Industry Numbers
4	1550	115	2103	49	0.3	CCWLE	3.6	3.4	3.8	1/4 x 20THD x 0.5	3	5212
4	1550	230	2122	50	0.2	CCWLE	3.6	3.4	3.8	1/4 x 20THD x 0.5	3	5222
5	1550	115	2120	67	0.6	CCWLE	3.6	3.4	3.8	1/4 x 20THD x 0.5	3	D583
6	1550	115	2116	50	0.4	CCWLE	3.6	3.8	4.3	1/4 x 20THD x 0.5	3	5312
9	1550	115	2118	51	0.6	CCWLE	3.6	3.8	4.3	1/4 x 20THD x 0.5	3.79	5412
9	1550	230	2109	56	0.3	CCWLE	3.6	3.8	4.3	1/4 x 20THD x 0.5	1.53	5422
16	1550	115	2111	71	1	CCWLE	3.6	4.1	4.5	1/4 x 20THD x 0.5	5	5812
16	1550	230	2113	72	0.5	CCWLE	3.6	4.1	4.5	1/4 x 20THD x 0.5	3.84	5822
25	1550	115	2124	158	1.1	CCWLE	3.9	4	4.5	1/4 x 20THD x 0.5	5	ESPL25EMR1
25	1550	230	2127	163	0.6	CCWLE	3.9	4	4.5	1/4 x 20THD x 0.5	2.2	ESPL25EMR2
35	1550	115	2128	158	1.4	CCWLE	3.9	4	4.5	1/4 x 20THD x 0.5	5	ESPL35EMR1
35	1550	230	2130	163	0.7	CCWLE	3.9	4	4.5	1/4 x 20THD x 0.5	5	ESPL35EMR2
50	1550	115	2132	182	1.7	CCWLE	4	4.7	6.2	0.375 x 1.5	6	ESPOL50EMR1
50	1550	230	2134	182	0.9	CCWLE	4	6.7	8.2	0.375 x 1.5	6.75	ESPOL50EMR2