
C-Flange Pool and Spa Motors
Switchless Design, 6.5" Frame Diameter, Category “C” & “J”



FEATURES:

- Two Compartment
- Shaft Threads - 7/16-20 UNF-2A
- 50°C Ambient
- 1081 Design
- Continuous Duty
- Class B Insulated
- Open Dripproof
- 300 Series Stainless Steel Shaft
- Thermally Protected
- Voltage Selection Device (Dual Voltage Only)
- 208v will not be marked on DOE regulated spread-voltage motors. Refer to online data
- **Discount symbol: DS-FPS**



- Optimized internal airflow design minimizes heat and moisture buildup inside the motor
- Internal bearing cover protects the drive/pump end ball bearing from water and debris that may occur inside of the motor
- Three additional layers of drive/pump end bearing protection:
  - Double Sealed Ball Bearing
  - Lip Seal
  - Water Slinger

Standard Efficient, Total Horsepower Rated

THP	RPM	Voltage	Freq	Amps	Shaft	Catalog Number	Motor Frame	Length Less Shaft	Wgt.	List	Notes
0.98	3450	230/115	60	5.4/10.8	Threaded	ASB126	56J	10.26	20	$241	
1.25	3450	230/115	60	7.0/14.0	Threaded	ASB127	56J	10.76	23	$268	
1.65	3450	230/115	60	7.7/15.4	Threaded	ASB128	56J	11.01	24	$307	
2.25	3450	230/115	60	10.8/21.6	Threaded	ASB129	56J	12.01	31	$415	
2.60	3450	230	60	11.5	Threaded	ASB130	56J	11.76	30	$497	

extreme-E Premium Energy Eff., Total Horsepower Rated (Suitable for 50Hz)**

THP	RPM	Voltage	Freq	Amps	Shaft	Catalog Number	Motor Frame	Length Less Shaft	Wgt.	List	Notes
0.98	3450	208-230/115	60	4.5-4.3/8.6	Keyed	ASB656	56C	10.51	20	$303	
0.98	3450	208-230/115	60	4.5-4.3/8.6	Threaded	ASB657	56J	10.51	20	$307	
1.25	3450	208-230/115	60	5.9-5.5/11.0	Threaded	ASB638	56J	11.01	23	$337	LA
1.65	3450	208-230/115	60	7.6-7.2/14.4	Keyed	ASB653	56C	11.26	25	$370	LA

Note LA Limited Availability
Note: Contact dealer for full conditions of operation
Catalog numbers are for competitive comparison purposes only.

extreme-E Extreme-E® represents one of our most efficient running, highest performing lines of motors.