
EFFECTIVE: 13-MAR-25	DIMENSION PRINT UNIMOUNT CCP W/AEGIS ON ODE & OVERSIZED O/B FRAME: 215JM BASIC TYPE: UTI4	PRINT: 07-3688-01
SUPERSEDES: NEW		SHEET: 1 OF 1



ALL DIMENSIONS ARE IN INCHES AND MILLIMETERS

	UNITS	A	B	C	D -.06	E	2E ±.03	2F ±.03	G	H +.05	J	K	O
	IN	9.50	8.88	21.38	5.25	4.25	8.50	7.00	.63	.44	1.19	1.56	10.25
	MM	241	226	543	133	108	216	178	16	11	30	40	260

	UNITS	P [2]	T	U -.0005	AA	AB	AC	AF	AG	AH ±.031	AJ	AK -.003	BA
	IN	11.25	.38	.8745	1.00	8.69	7.18	2.63	17.13	4.250	7.250	8.500	4.25
	MM	286	10	22.212		221	182	67	435	107.95	184.15	215.90	108

	UNITS	BB -.031	BC	BD MAX	BF [7]	BS	BV	EL -.002	EM -.0005	EN [7]	EP MIN	EQ ±.015	ER MIN
	IN	.373	.25	9.00	1/2-13 X .75	6.94	11.44	1.250	1.0000	3/8-16 X.75	1.75	.625	4.25
	MM	9.47	6	229		176	291	31.75	25.400		44	15.88	108

	UNITS	ES MIN	ET ±.015	EV	SQ KEY
	IN	1.66	2.875	.94	.188
	MM	42	73.03	24	4.78

TOLERANCES	
FACE RUNOUT	.004 T.I.R.
PERMISSIBLE ECCENTRICITY OF MOUNTING RABBET	.004 T.I.R.
PERMISSIBLE SHAFT RUNOUT	.002 T.I.R.

1. ALL ROUGH CASTING DIMENSIONS MAY VARY BY .25" DUE TO CASTING AND/OR FABRICATION VARIATIONS.
2. LARGEST MOTOR WIDTH.
3. FRAME REFERENCE: 9.500"/213 // 11.000"/215.
4. CONDUIT BOX MAY BE LOCATED ON EITHER SIDE OF MOTOR. CONDUIT OPENINGS MAY BE LOCATED IN STEPS OF 90 DEGREES REGARDLESS OF LOCATION. STANDARD AS SHOWN WITH CONDUIT OPENING DOWN.
5. TOLERANCES SHOWN ARE IN INCHES ONLY.
6. ALL TAPPED HOLES ARE UNIFIED NATIONAL COARSE, RIGHT HAND THREAD.
7. TAP SIZE AND BOLT PENETRATION ALLOWANCE.

07-3688/-

Nidec Motor Corporation
St. Louis, Missouri

INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION

ISSUED BY: S. RAMIREZ
APPROVED BY: L. SALAZAR

IHP_DP_NMCA (MAR-2011) SOLIDEDGE