

Special Application Close Coupled Pump Three Phase Open Dripproof (ODP) NEMA® Premium Efficient


NEMA
Premium

DE1

APPLICATIONS:

For the specific requirements of centrifugal pumps where the pump impeller is mounted directly on the motor shaft. Used where dirt and moisture are minimal.

FEATURES:

- Class F Insulation, Class B Rise At Service Factor
- Rolled Steel Frame
- Aluminum End Shields 140-250, Cast Iron End Shields 280-320
- Oversized Ball Bearings w/Locked Shaft End Construction
- Premasked Mylar Nameplate (with "CE" Mark)
- F1 Assembly Position
- Regreasable Bearings 180 Frame & Up, Lifting Provisions 210 Frame & Up
- Double Shielded Bearings
- 40°C Ambient, NEMA® Design B Performance On 60 Hertz Sine Wave Power
- "JM" Shaft For Mechanical Seal
- "JM" Shaft on 210 Frame and Smaller; "JP" Shaft on 250 and 280 Frame
- Conversion Kits: Canopy Kits

JM Shaft - Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes
3/4	1200	208-230/460	143JM	DJ34P3DM	\$655	DS-3POP	1.15	15.4	30	80.0	2.8-2.8/1.4	03
1	1800	200	143JM	DJ1P2HM	\$487	DS-3POP	1.15	15.4	30	85.5	3.6	
	1800	208-230/460	143JM	DJ1E2DM	\$455	DS-3FPO	1.15	15.4	30	82.5	3.1-3/1.5	16,NNP,LA
	1800	208-230/460	143JM	DJ1P2DM	\$487	DS-3POP	1.15	15.4	30	85.5	3.1-3.1/1.5	03
	1200	208-230/460	145JM	DJ1P3DM	\$655	DS-3POP	1.15	15.4	35	82.5	4-4/2	03
1 1/2	1800	200	145JM	DJ32P2HM	\$513	DS-3POP	1.15	14.75	35	85.5	4.8	
	3600	208-230/460	143JM	DJ32E1DM	\$491	DS-3FPO	1.15	15.4	30	82.5	4.3-4/2	16,NNP,LA
	3600	208-230/460	143JM	DJ32P1DM	\$519	DS-3POP	1.15	15.38	30	85.5	4.2-3.8/1.9	03
	1800	200	145JM	DJ32P2HM	\$513	DS-3POP	1.15	14.8	35	86.5	4.8	03
	1800	208-230/460	145JM	DJ32E2DM	\$468	DS-3FPO	1.15	15.4	35	84.0	4.5-4.4/2.2	16,NNP,LA
	1800	208-230/460	145JM	DJ32P2DM	\$513	DS-3POP	1.15	14.8	35	86.5	4.4-4.1/2.1	03
	1200	208-230/460	182JM	DJ32P3DM	\$660	DS-3POP	1.15	17.4	50	86.5	5-5/2.5	
2	3600	208-230/460	145JM	DJ2E1DM	\$524	DS-3FPO	1.15	15.4	35	84.0	5.6-5.1/2.5	16,NNP,LA
	3600	208-230/460	145JM	DJ2P1DM	\$567	DS-3POP	1.15	15.38	35	85.5	5.5-5/2.5	03
	1800	200	145JM	DJ2P2HM	\$563	DS-3POP	1.15	15.4	35	86.5	6.3	
	1800	208-230/460	145JM	DJ2E2DM	\$482	DS-3FPO	1.15	15.4	35	84.0	6-5.9/3	16,NNP,LA
	1800	208-230/460	145JM	DJ2P2DM	\$563	DS-3POP	1.15	14.8	35	86.5	5.9-5.6/2.8	03
	1800	575	145JM	DJ2E2GM	\$482	DS-3FPO	1.15	15.4	37	84.0	2.4	NNP,LA
	1800	575	145JM	DJ2P2GM	\$563	DS-3POP	1.15	15.38	35	86.5	2.2	
	1200	208-230/460	184JM	DJ2P3DM	\$739	DS-3POP	1.15	20.5	60	87.5	6.5-6.3/3.1	
3	3600	208-230/460	145JM	DJ3E1DM	\$550	DS-3FPO	1.15	15.4	35	84.0	8.3-7.5/3.7	16,NNP,LA
	3600	208-230/460	145JM	DJ3P1DM	\$582	DS-3POP	1.15	15.4	35	85.5	8.3-7.4/3.7	03
	1800	200	182JM	DJ3P2HM	\$598	DS-3POP	1.15	17.4	50	89.5	9	
	1800	208-230/460	182JM	DJ3E2DM	\$567	DS-3FPO	1.15	17.4	50	86.5	8.6-8.4/4.2	NNP,LA
	1800	208-230/460	182JM	DJ3P2DM	\$598	DS-3POP	1.15	17.4	50	89.5	8.4-7.8/3.9	
	1200	208-230/460	213JM	DJ3P3DM	\$941	DS-3POP	1.15	17.8	90	88.5	9.4-8.9/4.5	
5	3600	200	182JM	DJ5E1HM	\$718	DS-3FPO	1.15	17.4	50	85.5	14.8	NNP,LA
	3600	200	182JM	DJ5P1HM	\$620	DS-3POP	1.15	17.4	50	88.5	14.1	
	3600	208-230/460	182JM	DJ5E1DM	\$718	DS-3FPO	1.15	17.4	50	85.5	14.1-12.8/6.4	NNP,LA
	3600	208-230/460	182JM	DJ5P1DM	\$620	DS-3POP	1.15	16.1	50	88.5	13.5-12.3/6.2	
	3600	575	182JM	DJ5E1GM	\$718	DS-3FPO	1.15	17.4	50	85.5	5.1	NNP,LA
	1800	200	184JM	DJ5P2HM	\$645	DS-3POP	1.15	20.5	60	89.5	14.7	
	1800	208-230/460	184JM	DJ5E2DM	\$665	DS-3FPO	1.15	17.4	75	87.5	14-12.7/6.4	16,NNP,LA
	1800	208-230/460	184JM	DJ5P2DM	\$645	DS-3POP	1.15	20.5	60	89.5	13.8-13/6.5	03
	1200	208-230/460	215JM	DJ5P3DM	\$1,234	DS-3POP	1.15	19.3	105	89.5	15.2-14.5/7.3	
7 1/2	3600	208-230/460	184JM	DJ7E1DM	\$772	DS-3FPO	1.15	17.4	85	87.5	20.4-18.1/9.1	16,NNP,LA
	3600	208-230/460	184JM	DJ7P1DM	\$968	DS-3POP	1.15	17.4	60	88.5	20.5-18.1/9.1	03
	3600	575	184JM	DJ7E1GM	\$772	DS-3FPO	1.15	17.4	85	88.5	7.2	NNP,LA
	1800	200	213JM	DJ7P2HM	\$943	DS-3POP	1.15	17.8	90	91.0	21.4	
	1800	208-230/460	213JM	DJ7E2DM	\$882	DS-3FPO	1.15	17.8	113	88.5	21-19.2/9.6	NNP,LA

† All marks shown within this document are properties of their respective owners.

Revised — August 2016

Special Application Close Coupled Pump Three Phase Open Dripproof (ODP) NEMA® Premium Efficient



(continued)

DE1

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes
7 1/2	1800	208-230/460	213JM	DJ7P2DM	\$943	DS-3POP	1.15	17.8	90	91.0	20.2-18.5/9.3	03
	1800	575	213JM	DJ7E2GM	\$882	DS-3FPO	1.15	17.8	103	88.5	7.6	NNP,LA
	1800	575	213JM	DJ7P2GM	\$943	DS-3POP	1.15	17.75	90	91.0	7.3	
10	3600	200	213JM	DJ10P1HM	\$1,132	DS-3POP	1.15	17.8	90	90.2	28	03
	3600	208-230/460	213JM	DJ10E1DM	\$1,076	DS-3FPO	1.15	17.8	105	88.5	27.5-25.3/12.6	16,NNP,LA
	3600	208-230/460	213JM	DJ10P1DM	\$1,132	DS-3POP	1.15	17.8	90	90.2	27.1-24.3/12.2	03
	3600	575	213JM	DJ10E1GM	\$1,076	DS-3FPO	1.15	17.8	113	88.5	10.2	NNP,LA
	3600	575	213JM	DJ10P1GM	\$1,132	DS-3POP	1.15	17.75	90	90.2	9.7	
	1800	200	215JM	DJ10P2HM	\$1,147	DS-3POP	1.15	19.3	105	91.7	28.1	03
	1800	208-230/460	215JM	DJ10E2DM	\$1,036	DS-3FPO	1.15	19.3	190	89.5	27.2-24.6/12.3	16,NNP,LA
15	1800	208-230/460	215JM	DJ10P2DM	\$1,147	DS-3POP	1.15	19.3	105	92.4	26.3-23.8/11.9	03
	3600	208-230/460	215JM	DJ15E1DM	\$1,264	DS-3FPO	1.15	19.3	143	89.5	41-36/18.1	16,NNP,LA
	3600	208-230/460	215JM	DJ15P1DM	\$1,555	DS-3POP	1.15	19.25	105	90.2	40-36/18	03
20	1800	208-230/460	254JM	DJ15E2DM	\$1,372	DS-3FPO	1.15	24.6	172	91.0	41-38/19	16,NNP,LA
	3600	208-230/460	254JM	DJ20E1DM	\$1,611	DS-3FPO	1.15	24.6	170	90.2	54-47/23.6	16,NNP,LA
	3600	575	254JM	DJ20E1GM	\$1,611	DS-3FPO	1.15	24.6	170	90.2	18.9	NNP,LA
25	1800	208-230/460	256JM	DJ20E2DM	\$1,579	DS-3FPO	1.15	25.2	195	91.0	55-50/24.8	16,NNP,LA
	3600	208-230/460	256JM	DJ25E1DM	\$2,094	DS-3FPO	1.15	25.2	212	91.0	66-58/29	16,NNP,LA
	1800	208-230/460	284JM	DJ25E2DM	\$2,406	DS-3FPO	1.15	25.8	210	92.4	66-60/30	16,NNP,LA
30	1800	208-230/460	284JM	DJ25P2DM	\$2,435	DS-3POP	1.15	25.75	225	93.6	64-58/29	03
	3600	208-230/460	284JM	DJ30E1DM	\$3,193	DS-3FPO	1.15	25.8	230	91.0	80-70/35	16,NNP,LA
	3600	208-230/460	284JM	DJ30P1DM	\$2,901	DS-3POP	1.15	25.75	225	92.4	79-68/34	03
	1800	208-230/460	286JM	DJ30E2DM	\$2,767	DS-3FPO	1.15	25.8	280	92.4	78-71/35	16,NNP,LA
40	1800	208-230/460	286JM	DJ30P2DM	\$2,892	DS-3POP	1.15	25.75	250	94.1	77-69/34	03
	3600	208-230/460	286JM	DJ40E1DM	\$3,512	DS-3FPO	1.15	25.8	320	93.0	104-90/45	16,NNP,LA
	3600	208-230/460	286JM	DJ40P1DM	\$3,171	DS-3POP	1.15	25.75	250	93.0	104-90/45	03
	3600	575	286JM	DJ40E1GM	\$3,512	DS-3FPO	1.15	25.8	320	93.0	36	NNP,LA
	3600	575	286JM	DJ40P1GM	\$3,171	DS-3POP	1.15	25.75	250	93.0	36	
	1800	208-230/460	324JM	DJ40P2DM	\$3,178	DS-3POP	1.15	27.50	385	94.1	102-91/46	03
50	1800	230/460	324JM	DJ40E2EM	\$3,597	DS-3FPO	1.15	27.5	485	93.0	91/46	NNP,LA
	3600	208-230/460	324JM	DJ50P1DM	\$3,567	DS-3POP	1.15	27.50	385	93.0	130-117/59	03
	3600	230/460	324JM	DJ50E1EM	\$4,829	DS-3FPO	1.15	27.5	400	92.4	116/58	NNP,LA
	1800	208-230/460	326JM	DJ50P2DM	\$3,725	DS-3POP	1.15	27.50	460	94.5	126-113/56	03
60	1800	230/460	326JM	DJ50E2EM	\$4,137	DS-3FPO	1.15	27.5	450	93.6	114/57	17,NNP,LA
	3600	208-230/460	326JM	DJ60P1DM	\$4,916	DS-3POP	1.15	27.50	460	93.6	152-134/67	03
	3600	230/460	326JM	DJ60E1EM	\$5,553	DS-3FPO	1.15	27.5	460	93.0	136/68	17,NNP,LA

JP Shaft - Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes
1	1800	208-230/460	143JP	DJ1E2DP	\$455	DS-3FPO	1.15	17.8	32	82.5	3.1-3/1.5	16,NNP,LA
	1800	208-230/460	143JP	DJ1P2DP	\$487	DS-3POP	1.15	18.44	30	85.5	3.2-3.1/1.6	03
1 1/2	1800	208-230/460	145JP	DJ3P2DP	\$513	DS-3POP	1.15	18.44	35	86.5	4.4-4.2/2.1	03
2	1800	208-230/460	145JP	DJ2P2DP	\$563	DS-3POP	1.15	18.44	35	86.5	5.9-5.6/2.8	03
3	1800	208-230/460	182JP	DJ3E2DP	\$567	DS-3FPO	1.15	20.5	50	86.5	8.6-8.4/4.2	03,16,NNP,LA
5	1800	208-230/460	184JP	DJ5E2DP	\$665	DS-3FPO	1.15	20.5	75	87.5	14-12.7/6.4	16,NNP,LA
	1800	208-230/460	213JP	DJ7E2DP	\$882	DS-3FPO	1.15	21.6	90	88.5	21-19.2/9.6	NNP,LA
	1800	208-230/460	213JP	DJ7P2DP	\$943	DS-3POP	1.15	21.63	90	91.0	20.2-18.5/9.3	03
7 1/2	1200	208-230/460	254JP	DJ7P3DP	\$1,565	DS-3POP	1.15	27.4	150	91.0	20.5-18.9/9.5	03

† All marks shown within this document are properties of their respective owners.



Revised — August 2016

BRAKEMOTORS
GENERAL PURPOSE SINGLE PHASE
HVAC
WASHDOWN
AGRICULTURE
COMMERCIAL PUMP MOTORS
CLOSE COUPLED PUMP MOTORS
FIRE PUMP MOTORS
POOL & SPA MOTORS
RESIDENTIAL WATER PUMP
ELEVATOR GATE & DOOR
VARIABLE SPEED MOTORS AND DRIVES

Special Application Close Coupled Pump Three Phase Open Dripproof (ODP) NEMA® Premium Efficient


NEMA
Premium

DE1

(continued)

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes
10	3600	208-230/460	213JP	DJ10P1DP	\$1,132	DS-3POP	1.15	21.63	90	90.2	27.1-24.3/12.2	03
	1800	208-230/460	215JP	DJ10E2DP	\$1,036	DS-3FPO	1.15	23.1	100	89.5	27.2-24.6/12.3	16,NNP,LA
	1800	208-230/460	215JP	DJ10P2DP	\$1,147	DS-3POP	1.15	23.13	105	91.7	26.3-23.8/11.9	03
	1200	208-230/460	256JP	DJ10P3DP	\$2,036	DS-3POP	1.15	28.1	160	91.7	27.6-25.9/13	
15	3600	200	215JP	DJ15P1HP	\$1,555	DS-3POP	1.15	23.1	105	90.2	41	
	3600	208-230/460	215JP	DJ15E1DP	\$1,264	DS-3FPO	1.15	23.1	140	89.5	41-36/18.1	16,NNP,LA
	3600	208-230/460	215JP	DJ15P1DP	\$1,555	DS-3POP	1.15	23.1	105	90.2	40-36/18	
	1800	200	254JP	DJ15P2HP	\$1,569	DS-3POP	1.15	27.4	150	93.0	42	
	1800	208-230/460	254JP	DJ15E2DP	\$1,372	DS-3FPO	1.15	27.4	143	91.0	41-38/19	16,NNP,LA
	1800	208-230/460	254JP	DJ15P2DP	\$1,569	DS-3POP	1.15	27.4	150	93.0	40-37/18.5	
20	3600	200	254JP	DJ20P1HP	\$1,882	DS-3POP	1.15	27.44	150	91.0	54.0	
	3600	200	254JP	DJ20P1HP	\$1,882	DS-3POP	1.15	27.4	150	91.0	54.0	
	3600	208-230/460	254JP	DJ20E1DP	\$1,611	DS-3FPO	1.15	27.4	198	90.2	54-47/23.6	16,NNP,LA
	3600	208-230/460	254JP	DJ20P1DP	\$1,882	DS-3POP	1.15	27.4	150	91.7	52-47/23.4	
	3600	575	254JP	DJ20E1GP	\$1,611	DS-3FPO	1.15	27.4	195	90.2	18.9	NNP,LA
	1800	200	256JP	DJ20P2HP	\$2,012	DS-3POP	1.15	28.1	160	93.0	56	
	1800	208-230/460	256JP	DJ20E2DP	\$1,579	DS-3FPO	1.15	28.1	160	91.0	55-50/24.8	16,NNP,LA
	1800	208-230/460	256JP	DJ20P2DP	\$2,012	DS-3POP	1.15	28.1	160	93.0	53-48/24.2	
25	3600	200	256JP	DJ25P1HP	\$2,461	DS-3POP	1.15	28.1	160	92.4	67.0	
	3600	200	256JP	DJ25P1HP	\$2,461	DS-3POP	1.15	28.1	160	92.4	67.0	
	3600	208-230/460	256JP	DJ25E1DP	\$2,094	DS-3FPO	1.15	28.1	210	91.0	66-58/29	16,NNP,LA
	3600	208-230/460	256JP	DJ25P1DP	\$2,461	DS-3POP	1.15	28.1	160	91.7	65-57/28.7	03
	1800	200	284JP	DJ25P2HP	\$2,435	DS-3POP	1.15	28.6	225	93.6	67	
	1800	208-230/460	284JP	DJ25E2DP	\$2,406	DS-3FPO	1.15	28.6	213	92.4	66-60/30	16,NNP,LA
	1800	208-230/460	284JP	DJ25P2DP	\$2,435	DS-3POP	1.15	28.6	225	93.6	64-58/29.2	06
	1800	575	284JP	DJ25E2GP	\$2,406	DS-3FPO	1.15	28.6	213	91.7	24.4	NNP,LA
	1800	575	284JP	DJ25P2GP	\$2,435	DS-3POP	1.15	28.63	225	93.6	23.1	
30	3600	208-230/460	284JP	DJ30E1DP	\$3,193	DS-3FPO	1.15	28.6	230	91.0	80-70/35	16,NNP,LA
	3600	208-230/460	284JP	DJ30P1DP	\$2,901	DS-3POP	1.15	28.63	225	92.4	79-68/34	03
	1800	208-230/460	286JP	DJ30E2DP	\$2,767	DS-3FPO	1.15	28.6	230	92.4	78-71/35	16,NNP,LA
	1800	208-230/460	286JP	DJ30P2DP	\$2,892	DS-3POP	1.15	28.63	250	94.1	77-69/34	03
40	3600	208-230/460	286JP	DJ40E1DP	\$3,512	DS-3FPO	1.15	28.6	320	93.0	104-90/45	NNP,LA
	3600	208-230/460	286JP	DJ40P1DP	\$3,171	DS-3POP	1.15	28.63	250	93.0	104-90/45	03
	3600	575	286JP	DJ40E1GP	\$3,512	DS-3FPO	1.15	28.6	320	93.0	36	NNP,LA
	3600	575	286JP	DJ40P1GP	\$3,171	DS-3POP	1.15	28.63	250	93.0	36	
	1800	208-230/460	324JP	DJ40E2DP	\$3,597	DS-3FPO	1.15	30.4	412	93.6	102-91/46	17,NNP,LA
50	1800	208-230/460	324JP	DJ40P2DP	\$3,178	DS-3POP	1.15	30.38	454	94.1	102-91/46	03
	3600	208-230/460	324JP	DJ50P1DP	\$3,567	DS-3POP	1.15	30.38	454	93.0	130-117/59	03
	3600	230/460	324JP	DJ50E1EP	\$4,829	DS-3FPO	1.15	30.4	420	92.4	116/58	17,NNP,LA
	1800	208-230/460	326JP	DJ50P2DP	\$3,725	DS-3POP	1.15	30.38	454	94.5	126-113/56	03
60	1800	230/460	326JP	DJ50E2EP	\$4,137	DS-3FPO	1.15	30.4	460	93.6	114/57	17,NNP,LA
	3600	208-230/460	326JP	DJ60P1DP	\$4,915	DS-3POP	1.15	30.38	460	93.6	152-134/67	03
	3600	230/460	326JP	DJ60E1EP	\$5,553	DS-3FPO	1.25	30.4	460	93.0	136/68	17,NNP,LA

† All marks shown within this document are properties of their respective owners.

Revised — August 2016



Special Application Close Coupled Pump Three Phase Open Dripproof (ODP) NEMA[®] Premium Efficient



DE1

(continued)

Westcoast Shaft - Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes
7 1/2	1800	208-230/460	213TCZ	DJ7E2DJ	\$881	DS-3POV	1.15	18.8	105	88.5	21-19.2/9.6	NNP,LA
	1800	208-230/460	213TCZ	DJ7P2DJ	\$943	DS-3POP	1.15	20.81	90	91.0	20.2-18.5/9.3	03
10	3600	208-230/460	213TCZ	DJ10P1DJ	\$1,132	DS-3POP	1.15	20.81	90	90.2	27.1-24.3/12.2	03
	1800	208-230/460	215TCZ	DJ10P2DJ	\$1,147	DS-3POP	1.15	22.31	105	91.7	26.3-23.8/11.9	03
15	3600	208-230/460	215TCZ	DJ15P1DJ	\$1,555	DS-3POP	1.15	22.31	105	90.2	40-36/18	03

JM Shaft - Footless

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes
1	1800	208-230/460	143JM	DJ1E2DU	\$531	DS-3FPO	1.15	15.8	41	82.5	3.1-3/1.5	03,NNP,LA
	1800	208-230/460	143JM	DJ1P2DU	\$570	DS-3POV	1.15	15.61	30	85.5	3.2-3.1/1.6	03
1 1/2	3600	208-230/460	143JM	DJ32E1DU	\$576	DS-3FPO	1.15	15.8	41	82.5	4.3-4/2	03,NNP,LA
	3600	208-230/460	143JM	DJ32P1DU	\$609	DS-3POV	1.15	15.61	30	85.5	4.2-3.8/1.9	03
	1800	208-230/460	145JM	DJ32E2DU	\$548	DS-3FPO	1.15	15.8	40	84.0	4.5-4.4/2.2	03,NNP,LA
	1800	208-230/460	145JM	DJ32P2DU	\$581	DS-3POV	1.15	15.61	35	86.5	4.4-4.2/2.1	03
2	1800	208-230/460	145JM	DJ2E2DU	\$564	DS-3FPO	1.15	15.8	45	84.0	6-5.9/3	03,NNP,LA
	1800	208-230/460	145JM	DJ2P2DU	\$642	DS-3POV	1.15	15.61	35	86.5	5.9-5.6/2.8	03
3	1800	208-230/460	182JM	DJ3E2DU	\$665	DS-3POV	1.15	18.6	50	86.5	8.6-8.4/4.2	03,NNP,LA
5	1800	208-230/460	184JM	DJ5E2DU	\$778	DS-3POV	1.15	18.6	75	87.5	14-12.7/6.4	03,NNP,LA
7 1/2	3600	208-230/460	184JM	DJ7E1DU	\$987	DS-3POV	1.15	18.6	85	87.5	20.4-18.1/9.1	03,NNP,LA
	1800	208-230/460	213JM	DJ7P2DU	\$1,188	DS-3POV	1.15	18.63	90	91.0	20.2-18.5/9.3	03
10	3600	208-230/460	213JM	DJ10P1DU	\$1,420	DS-3POV	1.15	18.63	90	90.2	27.1-24.3/12.2	03
	1800	208-230/460	215JM	DJ10E2DU	\$1,213	DS-3POV	1.15	20.8	100	89.5	27.2-24.6/12.3	NNP,LA
	1800	208-230/460	215JM	DJ10P2DU	\$1,400	DS-3POV	1.15	18.75	105	91.7	26.3-23.8/11.9	03
15	3600	208-230/460	215JM	DJ15P1DU	\$1,809	DS-3POV	1.15	18.75	105	90.2	40-36/18	03
	1800	208-230/460	254JM	DJ15E2DU	\$1,655	DS-3POV	1.15	27.6	160	91.0	41-38/19	03,NNP,LA
20	3600	208-230/460	254JM	DJ20E1DU	\$1,942	DS-3POV	1.15	27.6	160	90.2	54-47/23.6	03,NNP,LA

Note 03 660/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate
 Note 16 Motors marked 208-230/460 volts may not meet all NEMA[®] (MG-1) performance standards when operated at 208 volts

Note 17 Twelve leads for across-the-line or wye-delta start on either voltage, part winding start on lower voltage
 Note LA Limited Availability
 Note NNP Non-NEMA[®] Premium

† All marks shown within this document are properties of their respective owners.



BRAKEMOTORS
 GENERAL PURPOSE SINGLE PHASE
 HVAC
 WASHDOWN
 AGRICULTURE
 COMMERCIAL PUMP MOTORS
 CLOSE COUPLED PUMP MOTORS
 FIRE PUMP MOTORS
 POOL & SPA MOTORS
 RESIDENTIAL WATER PUMP
 ELEVATOR GATE & DOOR
 VARIABLE SPEED MOTORS AND DRIVES