


# General Purpose Single Phase Open Drip-Proof (ODP), Split Phase



## APPLICATIONS:

For commercial and industrial ventilation systems.

## FEATURES:

- 40°C Ambient
- 60 Hz
- Reversible Rotation
- Continuous Duty
- Class A or B Insulation
- Ball Bearing

## Single Speed, Resilient Base

HP	RPM	Voltage	Frame	Catalog Number	SF	Shaft. Dim.	Total Length	Ship Wt.	Full Load Amps	Notes
1/6	1200	115	48Z	D16B3N4Z9	1.35	1/2" x 1.875"	10.4	17	4.5	20, 25
1/4	1800	115	48	D14B2N49	1.35	1/2" x 1.5"	8.4	14	5.1	25
	1800	115	56Z	D14B2NZA9	1.00	1/2" x 1.5"	9.4	15	5.4	20, 25
	1200	115	56	D14B3N9	1.35	5/8" x 1.875"	9.7	25	5.5	21, 25
	1200	208-230	56	7998	1.35	5/8" x 5.9"	14.0	25	2.9	24
1/3	1800	115	48	D13B2N4A9	1.00	1/2" x 1.5"	9.4	15	6.8	25
	1800	115	48Z	D13B2N4Z9	1.35	1/2" x 1.875"	9.3	16	7.0	20, 25
	1800	115	56Z	D13B2NZA9	1.00	1/2" x 1.875"	9.8	15	6	25
	1800	230	48	D13B2K4A9	1.00	1/2" x 1.5"	9.4	15	3	25
	1200	115/230	56	D13B3P9	1.35	1/2" x 1.5"	9.8	25	7.5/3.8	21, 25
1/2	1800	115	48	D12B2N49	1.00	1/2" x 1.5"	9.4	18	8.8	25
	1800	115	56	D12B2NA9	1.00	1/2" x 1.5"	9.7	21	8.6	25
	1800	115	56Z	D12B2NZA9	1.00	1/2" x 1.875"	9.1	18	6.0	25
3/4	1800	115	56	D34B2N9	1.00	5/8" x 1.875"	9.6	21	11.3	25

## Two Speed, Resilient Base

HP	RPM	Voltage	Frame	Catalog Number	SF	Shaft. Dim.	Total Length	Ship Wt.	Full Load Amps	Notes
1/3-1/9	1800/1200	115	48	D13B10N49	1.00	1/2" x 1.5"	10.4	19	6.4/4.0	20, 25
	1800/1200	115	56Z	3053	1.00	1/2" x 1.5"	9.9	19	7.1	25
1/2-1/6	1800/1200	115	56	3306	1.00	5/8" x 1.875"	10.8	26	9.2	25

## Single Speed, Rigid Base

HP	RPM	Voltage	Frame	Catalog Number	SF	Shaft Dim.	"C" Dim. (inches)	Ship Wt.	Full Load Amps	Notes
1/4	1800	115	48Z	D14B2N4Z	1.15	1/2" x 2.25"	9.3	14	5.3	20, 25
1/3	1800	115	48	D13B2N4A	1.00	1/2" x 1.5"	9.4	16	6.8	25
	1800	115	48	D13BA2N4A	1.35	1/2" x 1.5"	9.4	16	6.0	24
	1800	115	48Z	D13B2N4Z	1.35	1/2" x 2.25"	9.3	14	7.0	20, 25
	1800	115	56Z	2911	1.00	1/2" x 1.5"	9.4	17	6.0	25
1/2	1800	115	48	D12B2N4	1.00	1/2" x 1.5"	9.8	18	8.8	25
	1725	115	56	1366	1.25	5/8" x 1.875"	10.3	19	8.9	25

Note 20: Stud Extensions in 3 5/8" Square Pattern  
 Note 21: Stud Extensions in 4 3/16" Square Pattern  
 Note 24: Automatic Reset Thermal Overload Protector  
 Note 25: Non-Protected

† All marks shown within this document are properties of their respective owners.

