

General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Hostile Duty NEMA^{®†} Premium Efficient – IE3



NEMA
Premium

APPLICATIONS:

For pulp & paper plants, saw mills, mines, foundries, chemical plants, waste management facilities, and other process-related industries requiring protection within harsh operating conditions.

CTE

FEATURES:

- WORLDMOTOR[®] Features Except Where Noted
- Class F Insulation, Class B Rise At Full Load On 60 Hertz Sine Wave Power
- Cast Iron Frame (140: Rolled Steel), Cast Iron End Brackets
- Stainless Steel Nameplate (with "CE" Mark) & Zinc Plated Hardware
- Same Size Bearings (180 – 400 Frames)
- Shaft Slinger On Pulley End For IP54 Protection
- Dual Voltage 230/460 Volts (1-100 HP)
- 40°C Ambient, NEMA^{®†} Design B Performance On 60 Hertz Sine Wave Power
- Regreaseable Ball Bearings 250 Frame & Up, Lifting Provisions 180 Frame & Up
- Double Shielded Bearings 140-360, Open On 400-440
- 1.15 Service Factor @ 60 Hz
- Steel Fan Cover & Conduit Box
- Field Convertible To F2 Mounting 180 Frame & Larger
- Condensation Drains With Threaded Brass Breather Plugs
- Conversion Kits: All Cast Iron Upgrade, C&D Flanges, Canopy Kits (except 320-360)

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes
1	1800	200	143T	H1P2H	\$498	DS-3HD	12.9	45	85.5	3.4	
	1800	208-230/460	143T	H1P2D	\$498	DS-3HD	12.9	45	85.5	3.2-3/1.5	03
	1800	575	143T	H1P2G	\$498	DS-3HD	12.9	47	86.5	1.1	
	1200	208-230/460	145T	H1P3D	\$677	DS-3HD	13.1	52	82.5	3.6-3.5/1.8	03
	900	208-230/460	182T	H1E4D	\$1,049	DS-3HD	16.0	100	74.0	4.4-4.7/2.4	NNP
1 1/2	3600	200	143T	H32P1H	\$574	DS-3HD	12.9	45	84.0	4.4	
	3600	208-230/460	143T	H32P1D	\$574	DS-3HD	12.9	47	84.0	4.2-3.9/2	03
	1800	200	145T	H32P2H	\$552	DS-3HD	13.1	50	86.5	4.7	
	1800	208-230/460	145T	H32P2D	\$552	DS-3HD	13.1	52	86.5	4.5-4.3/2.1	03
	1800	575	145T	H32P2G	\$552	DS-3HD	13.1	52	86.5	1.7	
	1200	200	182T	H32P3H	\$751	DS-3HD	16.0	85	87.5	5.4	
	1200	208-230/460	182T	H32P3D	\$751	DS-3HD	16.0	138	87.5	4.8-4.7/2.3	03
	900	230/460	184T	H32E4E	\$1,164	DS-3HD	16.0	110	78.5	6.6/3.3	NNP
2	3600	200	145T	H2P1H	\$682	DS-3HD	13.1	50	86.5	5.6	
	3600	208-230/460	145T	H2P1D	\$682	DS-3HD	13.1	52	86.5	5.4-4.9/2.4	03
	3600	575	145T	H2P1G	\$682	DS-3HD	13.1	52	86.5	2	
	1800	200	145T	H2P2H	\$605	DS-3HD	13.1	50	86.5	6.2	03
	1800	208-230/460	145T	H2P2D	\$605	DS-3HD	13.1	50	86.5	6-5.7/2.8	03
	1800	575	145T	H2P2G	\$605	DS-3HD	13.1	52	86.5	2.3	
	1200	200	184T	H2P3H	\$836	DS-3HD	16.0	95	88.5	7.2	
	1200	208-230/460	184T	H2P3D	\$836	DS-3HD	16.0	95	88.5	6.4-6.2/3.1	03
	1200	575	184T	H2P3G	\$836	DS-3HD	16.0	95	88.5	2.5	
	900	230/460	213T	H2E4E	\$1,296	DS-3HD	19.2	160	82.5	7.6/3.8	03, NNP
900	575	213T	H2E4G	\$1,296	DS-3HD	19.2	160	82.5	3	NNP	
3	3600	200	182T	H3P1H	\$767	DS-3HD	16.0	85	86.5	8.8	
	3600	208/230	182T	H3P1D	\$767	DS-3HD	16.0	85	87.5	8.4/7.8	03
	3600	575	182T	H3P1G	\$767	DS-3HD	16.0	100	87.5	3.1	
	1800	200	182T	H3P2H	\$678	DS-3HD	16.0	85	89.5	9.1	
	1800	208-230/460	182T	H3P2D	\$678	DS-3HD	16.0	100	89.5	8.4-7.8/3.9	03
	1800	575	182T	H3P2G	\$678	DS-3HD	16.0	85	89.5	3.2	
	1200	200	213T	H3P3H	\$1,036	DS-3HD	19.2	150	89.5	10.1	
	1200	208-230/460	213T	H3P3D	\$1,036	DS-3HD	19.2	157	89.5	9.3-8.8/4.4	
	1200	575	213T	H3P3G	\$1,036	DS-3HD	19.2	157	89.5	3.5	
	900	200	215T	H3E4H	\$1,606	DS-3HD	19.2	180	84.0	12.8	NNP
	900	230/460	215T	H3E4E	\$1,606	DS-3HD	19.2	180	84.0	11.1/5.5	03, NNP
	900	575	215T	H3E4G	\$1,606	DS-3HD	19.2	180	84.0	4.5	NNP

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note NNP Non-NEMA^{®†} Premium Rating

† All marks shown within this document are properties of their respective owners.



GENERAL PURPOSE UNIMOUNT
GENERAL PURPOSE STEEL EDGE™
GENERAL PURPOSE HOSTILE DUTY
GENERAL PURPOSE CORRO-DUTY™
GENERAL PURPOSE 841 PLUS™
GENERAL PURPOSE OPEN DRIPPROOF
GENERAL PURPOSE HAZARDOUS LOCATION
GENERAL PURPOSE AUTOMOTIVE DUTY
COOLING TOWER DUTY
HAZARDOUS LOCATION
C-FACE MOTORS
VARIABLE FREQUENCY

General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Hostile Duty® NEMA® Premium Efficient – IE3 (continued)


NEMA
Premium

CTE

(continued)

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes
5	3600	200	184T	H5P1H	\$962	DS-3HD	16.0	100	88.5	14	
	3600	208-230/460	184T	H5P1D	\$962	DS-3HD	16.0	100	88.5	13.4-12.2/6.1	03
	3600	575	184T	H5P1G	\$962	DS-3HD	16.0	100	89.5	4.9	
	1800	200	184T	H5P2H	\$788	DS-3HD	16.0	100	89.5	14.6	
	1800	208-230/460	184T	H5P2D	\$788	DS-3HD	16.0	100	89.5	13.9-12.8/6.4	03
	1800	575	184T	H5P2G	\$788	DS-3HD	16.0	100	89.5	5.1	
	1200	200	215T	H5P3H	\$1,483	DS-3HD	19.2	150	89.5	15.9	
	1200	208-230/460	215T	H5P3D	\$1,483	DS-3HD	19.2	179	90.2	15-14/7	
	1200	575	215T	H5P3G	\$1,483	DS-3HD	19.2	150	90.2	5.6	
7 1/2	900	208-230/460	254T	H5E4D	\$2,299	DS-3HD	25.3	300	85.5	16.4-15.4/7.7	02,03,NNP
	3600	200	213T	H7P1H	\$1,192	DS-3HD	19.2	150	90.2	20.6	
	3600	208-230/460	213T	H7P1D	\$1,192	DS-3HD	19.2	160	91.0	19.9-17.8/8.9	03
	3600	575	213T	H7P1G	\$1,192	DS-3HD	19.2	160	91.7	7.1	14
	1800	200	213T	H7P2H	\$1,078	DS-3HD	19.2	150	91.7	21.5	
	1800	208-230/460	213T	H7P2D	\$1,078	DS-3HD	19.2	163	91.7	20-18.5/9.3	
	1800	575	213T	H7P2G	\$1,078	DS-3HD	19.2	163	91.7	7.5	
	1200	200	254T	H7P3H	\$1,979	DS-3HD	25.3	300	91.0	21.9	02
	1200	208-230/460	254T	H7P3D	\$1,979	DS-3HD	25.3	300	91.7	20.6-18.8/9.4	02
10	1200	575	254T	H7P3G	\$1,979	DS-3HD	25.3	300	91.0	7.6	02
	900	208-230/460	256T	H7E4D	\$3,067	DS-3HD	25.3	300	86.5	23.8-22.1/11	02,03,NNP
	3600	200	215T	H10P1H	\$1,397	DS-3HD	19.2	180	91.0	27	
	3600	208-230/460	215T	H10P1D	\$1,397	DS-3HD	19.2	180	91.7	26.4-23.5/11.8	
	3600	575	215T	H10P1G	\$1,397	DS-3HD	19.2	180	91.7	9.4	
	1800	200	215T	H10P2H	\$1,302	DS-3HD	19.2	190	91.7	27.5	
	1800	208-230/460	215T	H10P2D	\$1,302	DS-3HD	19.2	190	91.7	26.5-23.9/12	
	1800	575	215T	H10P2G	\$1,302	DS-3HD	19.1	195	91.7	9.6	
	1200	200	256T	H10P3H	\$2,390	DS-3HD	25.3	340	91.0	28.4	02
15	1200	208-230/460	256T	H10P3D	\$2,390	DS-3HD	25.3	340	91.7	27.1-24.6/12.3	02
	1200	575	256T	H10P3G	\$2,390	DS-3HD	25.3	340	91.7	9.8	02
	900	230/460	284T	H10E4E	\$3,693	DS-3HD	27.0	385	88.5	28.3/14.2	02,03,NNP
	900	575	284T	H10E4G	\$3,693	DS-3HD	27.0	340	88.5	11.4	02,NNP
	3600	200	254T	H15P1H	\$1,999	DS-3HD	25.3	300	91.0	40	02
	3600	208-230/460	254T	H15P1D	\$1,999	DS-3HD	25.3	300	91.0	39-34/17.2	02,03
	3600	575	254T	H15P1G	\$1,999	DS-3HD	25.3	300	91.0	13.8	02
	1800	200	254T	H15P2H	\$1,798	DS-3HD	25.3	300	92.4	42	02
	1800	208-230/460	254T	H15P2D	\$1,798	DS-3HD	25.3	300	92.4	40-37/18.4	02
COOLING TOWER DUTY	1800	575	254T	H15P2G	\$1,798	DS-3HD	25.3	300	92.4	14.6	
	1200	200	284T	H15P3H	\$3,331	DS-3HD	27.0	385	91.7	42	02,14
	1200	208-230/460	284T	H15P3D	\$3,331	DS-3HD	27.0	385	91.7	41-37/18.4	02,03,14
	1200	575	284T	H15P3G	\$3,331	DS-3HD	27.0	284	91.7	14.8	02,14
	900	200	286T	H15E4H	\$4,938	DS-3HD	27.0	390	88.5	50	02,NNP
	900	230/460	286T	H15E4E	\$4,938	DS-3HD	27.0	390	88.5	44/21.8	02,03,NNP
	900	575	286T	H15E4G	\$4,938	DS-3HD	27.0	390	88.5	17.3	02,NNP

Note 02 Suitable for Wye-Delta start on voltages shown
 Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note 14 NEMA® Design A
 Note NNP Non-NEMA® Premium Rating

† All marks shown within this document are properties of their respective owners.



General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Hostile Duty® NEMA® Premium Efficient – IE3 (continued)



NEMA
Premium

(continued)

CTE

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes
20	3600	200	256T	H20P1H	\$2,475	DS-3HD	25.3	340	91.0	53	02
	3600	208-230/460	256T	H20P1D	\$2,475	DS-3HD	25.3	340	91.0	53-46/23	02,03
	3600	575	256T	H20P1G	\$2,475	DS-3HD	25.3	340	91.0	18.4	02
	1800	200	256T	H20P2H	\$2,216	DS-3HD	25.3	340	93.0	54	02
	1800	208-230/460	256T	H20P2D	\$2,216	DS-3HD	25.3	340	93.0	53-47/23.5	02,03
	1800	575	256T	H20P2G	\$2,216	DS-3HD	25.3	340	93.0	19	02
	1200	200	286T	H20P3H	\$4,035	DS-3HD	27.0	286	91.7	57	02,14
	1200	208-230/460	286T	H20P3D	\$4,035	DS-3HD	27.0	400	91.7	54-49/24.5	02,03,14
	1200	575	286T	H20P3G	\$4,035	DS-3HD	27.0	400	91.7	19.7	02,14
	900	230/460	324T	H20E4E	\$5,844	DS-3HD	30.6	510	89.5	55/27.3	02,03,NNP
900	575	324T	H20E4G	\$5,844	DS-3HD	30.6	510	89.5	21.7	02,NNP	
25	3600	200	284TS	H25P1HS	\$3,036	DS-3HD	25.6	355	91.7	67	02
	3600	208-230/460	284T	H25P1D	\$3,036	DS-3HD	27.0	355	91.7	66-57/28.7	02,03
	3600	208-230/460	284TS	H25P1DS	\$3,036	DS-3HD	25.6	355	91.7	66-57/28.7	02,03
	3600	575	284TS	H25P1GS	\$3,036	DS-3HD	25.6	355	91.7	23	02
	1800	200	284T	H25P2H	\$2,659	DS-3HD	27.0	355	93.6	66	02
	1800	200	284TS	H25P2HS	\$2,659	DS-3HD	25.6	355	93.6	66	02
	1800	208-230/460	284T	H25P2D	\$2,659	DS-3HD	27.0	355	93.6	64-58/28.9	02,03
	1800	208-230/460	284TS	H25P2DS	\$2,659	DS-3HD	25.6	355	93.6	64-58/28.9	02,03
	1800	575	284T	H25P2G	\$2,659	DS-3HD	27.0	355	93.6	23	02
	1800	575	284TS	H25P2GS	\$2,659	DS-3HD	25.6	355	93.6	23	02
	1200	200	324T	H25P3H	\$4,801	DS-3HD	30.6	510	93.0	71	02,14
	1200	230/460	324T	H25P3E	\$4,801	DS-3HD	30.6	510	93.0	62/31	02,03,14
	1200	575	324T	H25P3G	\$4,801	DS-3HD	30.6	510	93.0	24.6	02,14
	900	200	326T	H25E4H	\$6,923	DS-3HD	30.6	590	89.5	78	02,NNP
	900	230/460	326T	H25E4E	\$6,923	DS-3HD	30.6	590	89.5	67/33	02,03,NNP
30	3600	200	286TS	H30P1HS	\$3,560	DS-3HD	25.6	400	91.7	79	02
	3600	208-230/460	286T	H30P1D	\$3,560	DS-3HD	27.0	400	91.7	79-69/34	02,03
	3600	208-230/460	286TS	H30P1DS	\$3,560	DS-3HD	25.6	400	91.7	79-69/34	02,03
	3600	575	286TS	H30P1GS	\$3,560	DS-3HD	25.6	400	91.7	27.6	02
	1800	200	286T	H30P2H	\$3,101	DS-3HD	27.0	415	93.6	80	02
	1800	200	286TS	H30P2HS	\$3,101	DS-3HD	25.6	415	93.6	80	02
	1800	208-230/460	286T	H30P2D	\$3,101	DS-3HD	27.0	415	93.6	77-69/35	03
	1800	208-230/460	286TS	H30P2DS	\$3,101	DS-3HD	25.6	415	93.6	77-69/35	03
	1800	575	286T	H30P2G	\$3,101	DS-3HD	27.0	415	93.6	27.6	02
	1800	575	286TS	H30P2GS	\$3,101	DS-3HD	25.6	415	93.6	27.6	02
	1200	200	326T	H30P3H	\$5,665	DS-3HD	30.6	590	93.0	84	02,14
	1200	230/460	326T	H30P3E	\$5,665	DS-3HD	30.6	590	93.0	74/37	02,03,14
	1200	575	326T	H30P3G	\$5,665	DS-3HD	30.6	590	93.0	29.6	02,14
	900	230/460	364T	H30E4E	\$7,970	DS-3HD	32.6	790	91.7	80/40	02,03,NNP
900	575	364T	H30E4G	\$7,970	DS-3HD	32.6	790	92.4	31	02,NNP	

Note 02 Suitable for Wye-Delta start on voltages shown
 Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note 14 NEMA® Design A
 Note NNP Non-NEMA® Premium Rating

† All marks shown within this document are properties of their respective owners.



GENERAL PURPOSE UNIMOUNT
 GENERAL PURPOSE STEEL EDGE™
 GENERAL PURPOSE HOSTILE DUTY
 GENERAL PURPOSE CORRO-DUTY™
 GENERAL PURPOSE 84 PLUS™
 GENERAL PURPOSE OPEN DRIPPROOF
 GENERAL PURPOSE HAZARDOUS LOCATION
 GENERAL PURPOSE AUTOMOTIVE DUTY
 COOLING TOWER DUTY
 HAZARDOUS LOCATION
 C-FACE MOTORS
 VARIABLE FREQUENCY

General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Hostile Duty® NEMA® Premium Efficient – IE3 (continued)


**NEMA
Premium**

(continued)

CTE

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes	
40	3600	200	324TS	H40P1HS	\$4,600	DS-3HD	29.1	460	93.0	104	02,14	
	3600	230/460	324TS	H40P1ES	\$4,600	DS-3HD	29.1	460	93.0	90/45	02,03,14	
	3600	575	324TS	H40P1GS	\$4,600	DS-3HD	29.1	460	93.0	36	02,14	
	1800	200	324T	H40P2H	\$4,049	DS-3HD	30.6	510	94.1	104	02	
	1800	200	324TS	H40P2HS	\$4,049	DS-3HD	29.1	510	94.1	104	02	
	1800	230/460	324T	H40P2E	\$4,049	DS-3HD	30.6	510	94.1	90/45	02,03	
	1800	230/460	324TS	H40P2ES	\$4,049	DS-3HD	29.1	510	94.1	90/45	02,03	
	1800	575	324T	H40P2G	\$4,049	DS-3HD	30.6	510	94.1	36	02	
	1800	575	324TS	H40P2GS	\$4,049	DS-3HD	29.1	510	94.1	36	02	
	1200	200	364T	H40P3H	\$7,630	DS-3HD	32.6	800	94.1	106	02	
	1200	230/460	364T	H40P3E	\$7,630	DS-3HD	32.6	800	94.1	93/46	02,03	
	1200	575	364T	H40P3G	\$7,630	DS-3HD	32.6	800	94.1	37	02	
50	900	230/460	365T	H40E4E	\$9,873	DS-3HD	32.6	840	92.4	105/52	02,03,NNP	
	900	575	365T	H40E4G	\$9,873	DS-3HD	32.6	840	92.4	41	02,NNP	
	3600	200	326TS	H50P1HS	\$5,919	DS-3HD	29.1	550	93.0	129	02	
	3600	230/460	326TS	H50P1ES	\$5,919	DS-3HD	29.1	550	93.0	112/56	02,03	
	3600	575	326TS	H50P1GS	\$5,919	DS-3HD	29.1	550	93.0	45	02	
	1800	200	326T	H50P2H	\$4,971	DS-3HD	30.6	590	94.5	129	02,14	
	1800	200	326TS	H50P2HS	\$4,971	DS-3HD	29.1	590	94.5	129	02,14	
	1800	230/460	326T	H50P2E	\$4,971	DS-3HD	30.6	590	94.5	112/56	02,03	
	1800	230/460	326TS	H50P2ES	\$4,971	DS-3HD	29.1	590	94.5	112/56	02,03	
	1800	575	326T	H50P2G	\$4,971	DS-3HD	30.6	590	94.5	45	02	
	1800	575	326TS	H50P2GS	\$4,971	DS-3HD	29.1	590	94.5	45	02	
	1200	200	365T	H50P3H	\$8,790	DS-3HD	32.6	890	94.1	133	02	
1200	230/460	365T	H50P3E	\$8,790	DS-3HD	32.6	890	94.1	115/58	02,03		
1200	575	365T	H50P3G	\$8,790	DS-3HD	32.6	890	94.1	46	02		
60	3600	200	364TS	H60P1HS	\$7,901	DS-3HD	30.4	825	93.6	154	02,14	
	3600	230/460	364TS	H60P1ES	\$7,901	DS-3HD	30.4	825	93.6	134/67	02,03	
	3600	575	364TS	H60P1GS	\$7,901	DS-3HD	30.4	825	93.6	53	02,14	
	1800	200	364T	H60P2H	\$7,228	DS-3HD	32.6	865	95.0	155	02	
	1800	200	364TS	H60P2HS	\$7,228	DS-3HD	30.4	865	95.0	155	02	
	1800	230/460	364T	H60P2E	\$7,228	DS-3HD	32.6	865	95.0	136/68	02,03	
	1800	230/460	364TS	H60P2ES	\$7,228	DS-3HD	30.4	865	95.0	136/68	02,03	
	1800	575	364T	H60P2G	\$7,228	DS-3HD	32.6	865	95.0	55	02	
	1800	575	364TS	H60P2GS	\$7,228	DS-3HD	30.4	865	95.0	55	02	
	1200	230/460	404T	H60P3E	\$10,356	DS-3HD	37.6	1160	94.5	139/70		
	75	3600	200	365TS	H75P1HS	\$9,928	DS-3HD	30.4	875	93.6	194	02,14
		3600	230/460	365TS	H75P1ES	\$9,928	DS-3HD	30.4	875	93.6	167/84	02,03,14
3600		575	365TS	H75P1GS	\$9,928	DS-3HD	30.4	875	93.6	67	02,14	
1800		200	365T	H75P2H	\$9,193	DS-3HD	32.6	890	95.4	196	02,14	
1800		200	365TS	H75P2HS	\$9,193	DS-3HD	30.4	890	95.4	196	02,14	
1800		230/460	365T	H75P2E	\$9,193	DS-3HD	32.6	890	95.4	169/85	02,03	
1800		230/460	365T	H75P2EB	\$9,730	DS-3HD	32.6	890	95.4	169/85	02,03,09	
1800		230/460	365TS	H75P2ES	\$9,193	DS-3HD	30.4	890	95.4	169/85	02,03	
1800		575	365T	H75P2G	\$9,193	DS-3HD	32.6	890	95.4	68	02	
1800		575	365T	H75P2GB	\$9,730	DS-3HD	32.6	890	95.4	68	02,09	
1800		575	365TS	H75P2GS	\$9,193	DS-3HD	30.4	890	95.4	68	02	
1200		230/460	405T	H75P3E	\$12,210	DS-3HD	37.6	1175	94.5	174/87	02,03	

Note 02 Suitable for Wye-Delta start on voltages shown
 Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note 09 Roller Bearing
 Note 14 NEMA® Design A
 Note NNP Non-NEMA® Premium Rating

† All marks shown within this document are properties of their respective owners.



General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Hostile Duty® NEMA® Premium Efficient – IE3 (continued)



NEMA
Premium

(continued)

CTE

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes
75	1200	230/460	405T	H75P3EB	\$13,310	DS-3HD	37.6	1175	94.5	174/87	02,03,09
	900	230/460	444T	H75E4E	\$18,164	DS-3HD	45.8	1400	93.0	193/97	02,03,NNP
100	3600	230/460	405TS	H100P1ES	\$13,296	DS-3HD	34.6	1175	94.5	224/112	02,03
	3600	575	405TS	H100P1GS	\$13,296	DS-3HD	34.6	1175	94.1	90	
	1800	200	405T	H100P2H	\$11,329	DS-3HD	37.6	1200	95.4	260	
	1800	200	405TS	H100P2HS	\$11,329	DS-3HD	34.6	1200	95.4	260	
	1800	230/460	405T	H100P2E	\$11,329	DS-3HD	37.6	1200	95.4	225/113	
	1800	230/460	405T	H100P2EB	\$12,429	DS-3HD	37.6	1200	95.4	225/113	09
	1800	230/460	405TS	H100P2ES	\$11,329	DS-3HD	34.6	1200	95.4	225/113	
	1800	575	405T	H100P2G	\$11,329	DS-3HD	37.6	1200	95.4	90	02
	1800	575	405T	H100P2GB	\$11,939	DS-3HD	37.6	1200	95.4	90	02,09
	1800	575	405TS	H100P2GS	\$11,329	DS-3HD	34.6	1200	95.4	90	
	1200	230/460	444T	H100P3E	\$16,718	DS-3HD	45.8	1600	95.4	248/124	02,03
	1200	230/460	444T	H100P3EB	\$18,268	DS-3HD	45.8	1600	95.4	248/124	02,03,09
	1200	575	444T	H100P3G	\$16,718	DS-3HD	43.4	1618	95.4	99	
	1200	575	444T	H100P3GB	\$17,868	DS-3HD	45.8	1600	95.0	99	02,09
	900	230/460	445T	H100E4E	\$22,950	DS-3HD	45.4	1500	93.6	262/131	02,03,NNP
125	3600	460	444TS	H125P1FS	\$16,545	DS-3HD	41.66	1550	95.8	142	03
	3600	575	444TS	H125P1GS	\$16,545	DS-3HD	41.66	1550	95.8	114	
	1800	460	444T	H125P2F	\$14,102	DS-3HD	45.8	1575	95.4	144	02,03
	1800	460	444T	H125P2FB	\$15,652	DS-3HD	45.8	1575	95.4	144	02,03,09
	1800	460	444TS	H125P2FS	\$14,102	DS-3HD	42.0	1575	95.4	144	02
	1800	575	444T	H125P2G	\$14,102	DS-3HD	45.8	1575	95.4	116	02
	1800	575	444TS	H125P2GS	\$14,102	DS-3HD	42.0	1575	95.4	116	02
	1200	460	445T	H125P3F	\$19,123	DS-3HD	45.8	1650	95.4	151	02,03
	1200	460	445T	H125P3FB	\$20,673	DS-3HD	45.8	1650	95.4	151	02,09
	1200	575	445T	H125P3G	\$19,123	DS-3HD	45.8	1650	95.4	123	02
	1200	575	445T	H125P3GB	\$20,273	DS-3HD	45.8	1650	95.4	123	02,09
	900	460	447T	H125E4F	\$25,055	DS-3HD	48.9	1900	94.1	155	02,03,NNP
150	3600	460	445TS	H150P1FS	\$20,361	DS-3HD	41.66	1625	95.8	171	03
	3600	575	445TS	H150P1GS	\$20,361	DS-3HD	41.66	1625	95.4	137	
	1800	460	445T	H150P2F	\$16,738	DS-3HD	45.8	1650	95.8	171	02,03
	1800	460	445T	H150P2FB	\$18,288	DS-3HD	45.8	1650	95.8	171	02,03,09
	1800	460	445TS	H150P2FS	\$16,738	DS-3HD	42.0	1650	95.8	171	02
	1800	575	445T	H150P2G	\$16,738	DS-3HD	45.8	1650	95.8	137	02
	1800	575	445TS	H150P2GS	\$16,738	DS-3HD	42.0	1650	95.8	137	02
	1200	460	447T	H150P3F	\$21,964	DS-3HD	49.3	2000	96.2	181	02,03
	1200	460	447T	H150P3FB	\$23,514	DS-3HD	49.3	2000	96.2	181	02,09
	1200	575	447T	H150P3G	\$21,964	DS-3HD	49.3	2000	95.8	145	02
	1200	575	447T	H150P3GB	\$23,314	DS-3HD	49.3	2000	95.8	145	02,09
	200	3600	460	447TS	H200P1FS	\$25,731	DS-3HD	45.16	2100	96.2	217
3600		575	447TS	H200P1GS	\$25,731	DS-3HD	45.16	2100	95.8	173	
1800		460	447T	H200P2F	\$20,393	DS-3HD	49.3	2150	96.2	224	02,03
1800		460	447T	H200P2FB	\$21,943	DS-3HD	49.3	2150	96.2	224	02,03,09
1800		460	447TS	H200P2FS	\$20,393	DS-3HD	45.5	2150	96.2	224	02
1800		575	447T	H200P2G	\$20,393	DS-3HD	49.3	2150	96.2	181	02
1800		575	447TS	H200P2GS	\$20,393	DS-3HD	45.5	2150	96.2	181	02

Note 02 Suitable for Wye-Delta start on voltages shown
 Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note 09 Roller Bearing
 Note NNP Non-NEMA® Premium Rating

† All marks shown within this document are properties of their respective owners.



GENERAL PURPOSE UNIMOUNT
 GENERAL PURPOSE STEEL EDGE™
 GENERAL PURPOSE HOSTILE DUTY
 GENERAL PURPOSE CORRO-DUTY™
 GENERAL PURPOSE 841 PLUS™
 GENERAL PURPOSE OPEN DRIPPROOF
 GENERAL PURPOSE HAZARDOUS LOCATION
 GENERAL PURPOSE AUTOMOTIVE DUTY
 COOLING TOWER DUTY
 HAZARDOUS LOCATION
 C-FACE MOTORS
 VARIABLE FREQUENCY