Fast TrakTM

The ideal overpour installation method for remodel and retrofit applications

The preformed knobbed panels make it easy to install $\frac{5}{16}$ ", $\frac{3}{8}$ " or $\frac{1}{2}$ " Wirsbo hePEXTM tubing for radiant floor heating systems.

From basement remodels to new construction to retrofit applications, you can quickly and easily install a radiant floor heating system with Uponor's Fast $Trak^{TM}$.

Simply place the preformed panels on the subfloor or slab and snap in Uponor's crosslinked polyethylene (PEX) tubing between the knobs for a fast and easy overpour installation method.

Fast Trak Products

Part No.	Product	Insulation	Adhesive Backing	Tubing Size	Features and Advantages
A5090313	Fast Trak 0.5		X	5/16"	½" height, ideal for retrofits
A5090500	Fast Trak 1.3i	X		³⁄8" and ½"	Just over 1½" height; includes insulation under the panel

For more information, visit www.uponorpro.com/radiantready.

Uponor, Inc.

5925 148th Street West Apple Valley, MN 55124 USA Tel: 800.321.4739 Fax: 952.891.2008

Web: www.uponor-usa.com

Uponor Ltd.

2000 Argentia Rd., Plaza 1, Ste. 200 Mississauga, ON L5N 1W1 CANADA Tel: 888.994.7726 Fax: 800.638.9517

Web: www.uponor.ca