


FILAMENT TAPE

Venture Tape® 205 is a glass filament reinforced tape for light duty strapping, bundling and reinforcing. It has a synthetic rubber resin adhesive with good adhesion to most fiberboard surfaces, and a variety of plastics and metal surfaces.

Application of Venture Tape® 205 is most easily accomplished at room temperature. At lower temperatures approaching 32°F (0°C), the adhesive becomes firm. Once applied, 205 performs well throughout the normal temperature ranges typically encountered in temporary holding applications on construction sites.

Product Construction





Features & Benefits

- Abrasion and moisture resistant
- High tensile strength
- Allows printing and illustrations to be seen through tape
- Good shear and initial adhesion
- Good aging

	Typical Value		
Test	Typical Value	(Metric)	Test Method
Product Thickness (Total)	4.0 mils	101.6 microns	PSTC-133
Peel Adhesion	60 oz/in	16.7 N/25mm	PSTC-101
Tensile Strength	100 lb/in	445 N/25mm	PSTC-131
Elongation	3 %	3 %	

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Product Configurations

Width (mm)	<u>Length (m)</u>	Rolls/case
18	55	48
24	55	36

Contact Venture Tape today for a complete list of products or a free sample

Toll Free North America 800-343-1076
From United Kingdom 0-800-962-957
From Australia 1-800-122-797
www.venturetape.com



USA

Venture Tape Corp. 30 Commerce Road Rockland, MA 02370 781-331-5900 FAX 781-871-0065

Europe – Venture Tape

Venture Tape Europe Corp. Units 5 – 6, Faraday Close, Drayton Fields, Daventry, Northamptonshire, England NN11 8RD (0) 1327 876555 FAX (0) 1327 876444

Australasia

Venture Tape Australasia, Pty., Ltd. 11B Production Drive Campbellfield 3061 Victoria Australia (03) 9357 6025 FAX (03) 9357 6045