



Item includes



Item No.: 2773-500

2

Mounting carrier; for single- and double-row con.; 2773 Series; for DIN-35 rail mounting/screw mounting; orange



Item No.: 2773-402

COMPACT splicing connector; for solid and stranded conductors; max. 4 mm²; 2-conductor; transparent housing; white cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent



Item No.: 2773-408

8

COMPACT splicing connector; for solid and stranded conductors; max. 4 mm²; 8-conductor; transparent housing; light gray cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent



Item No.: 2773-403

30

COMPACT splicing connector; for solid and stranded conductors; max. 4 mm²; 3-conductor; transparent housing; orange cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent



Item No.: 2773-404

COMPACT splicing connector; for solid and stranded conductors; max. 4 mm²; 4-conductor; transparent housing; red cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent



Item No.: 2773-405

COMPACT splicing connector; for solid and stranded conductors; max. 4 mm²; 5-conductor; transparent housing; yellow cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent



Item No.: 2773-406

10

COMPACT splicing connector; for solid and stranded conductors; max. 4 mm²; 6-conductor; transparent housing; Gray cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent

Physical data

Width	250 mm / 9.843 inches
Height	42 mm / 1.654 inches
Depth	106 mm / 4.173 inches

Material Data

Note (material data)

[Information on material specifications can be found here](#)

Fire load	1.3 MJ
Weight	428.1 g

Commercial data	
ETIM 8.0	EC000446
ETIM 7.0	EC000446
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143950909
Customs tariff number	85369010000

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 887-800	

Documentation

Additional Information		
Technical Section	pdf 2142.18 KB	