



Job Name: _____

Job Location: _____

Contractor: _____

Engineer: _____

Approval: _____

Plumerex® ADA-Approved Undersink Protective Covers

Design Features:

- White Soft PVC Construction
- UV Inhibited
- Anti-Microbial
- Anti-Fungal
- Tamper Resistant
- Velcro Fasteners
- Made in the USA

Use: Insulates drain and supply lines under lavatories to protect persons confined to wheelchairs from bruising, cutting, or burning their legs, making existing installation ADA Compliant.



ADA 4.19.4/ABA 606.5, ICC/ANSI A 117.1 (606.6) IBC (International Building Code)
Chapter 8
UPC/IAPMO 94-2008

ASTM E 84-07 (Class A Insulation Material) 25 Flame Spread/450 Smoke Index

ASTM C-177 Thermal Conductivity 0.028 (K-Value) Thermal Resistance .504 (R-Value)

ASTM C-518 Thermal Conductivity 0.358 (avg.) Thermal Resistance .346 (avg.)
Thermal Resistance 2.790 ("R" per inch)

Density 21.61 (PCF)

ASTM G153, D412, D570. Tested for long term degradation.

ASTM G153. Weatherization & UV

ASTM D 412. Tensile Strength and Elongation

ASTM D570. Water Absorption

ASTM G21. Interior and Exterior surface tested Result of -0- Fungal/Microbial Growth.



Includes covers
for trap, 2 stops
and 2 risers

W-R#	Description	Weight	Min	Box
1863002	White Plumerex® Trap Gear	.603 lbs.	1	25