

BALL VALVES

PATENTS PENDING

FULL PORT FORGED BRASS BALL VALVE

w/ Adjustable Packing Gland

STANDARD BRASS

Certified to NSF/ANSI 61-8

SIZE	ITEM#	CTN/CASE	CASE WT	ITEM#	CTN/CASE	CASE WT
FIP						
w/ Chrome-Plated Lever Handle 600 PSI CWP Max/150 WSP (400 PSI CWP Max/125 WSP 2½"-4")						
1/4"	H-41700	10/100	27	H-41700W	10/100	27
3/8"	H-41701	10/100	29	H-41701W	10/100	29
1/2"	H-41702	10/80	32	H-41702W	10/80	31
3/4"	H-41703	10/60	35	H-41703W	10/60	35
1"	H-41704	6/36	39	H-41704W	6/36	38
1 1/4"	H-41705	6/24	35	H-41705W	6/24	35
1 1/2"	H-41706	2/16	36	H-41706W	2/16	36
2"	H-41707	2/12	38	H-41707W	2/12	38
2 1/2"	H-41708	1/6	43	H-41708W	1/6	45
3"	H-41709	1/4	37	H-41709W	1/4	36
4"	H-41710	1/2	31	H-41710W	1/2	30

CERTIFICATIONS DO NOT APPLY TO 41708, 41709, 41710

w/ 304 Stainless Steel Handle

600 PSI CWP Max/150 WSP						
1/2"	H-41702SSL	10/80	31	H-41702WSSL	10/80	31
3/4"	H-41703SSL	10/60	35	H-41703WSSL	10/60	36
1"	H-41704SSL	6/36	39	H-41704WSSL	6/36	39
1 1/4"	H-41705SSL	6/24	34	H-41705WSSL	6/24	34
1 1/2"	H-41706SSL	2/16	40	H-41706WSSL	2/16	36
2"	H-41707SSL	2/12	38	H-41707WSSL	2/12	38

w/ Wing Style "T" Handle

600 PSI CWP Max/150 WSP						
1/2"	H-41702T	10/80	33	H-41702WT	10/80	33
3/4"	H-41703T	10/60	35	H-41703WT	10/60	38
1"	H-41704T	6/36	44	H-41704WT	6/36	40

w/ 304 Stainless Steel Wing Style "T" Handle

600 PSI CWP Max/150 WSP						
1/2"	H-41702SSW	10/80	39	H-41702WSSW	10/80	39
3/4"	H-41703SSW	10/60	36	H-41703WSSW	10/60	36
1"	H-41704SSW	6/48	55	H-41704WSSW	6/48	52

STANDARD BRASS

Certified to NSF/ANSI 61-8

SIZE	ITEM#	CTN/CASE	CASE WT	ITEM#	CTN/CASE	CASE WT
SWT						
w/ Chrome-Plated Lever Handle 600 PSI CWP Max/150 WSP (400 PSI CWP Max/125 WSP 2½"-4")						
1/2"	H-51702	10/80	27	H-51702W	10/80	26
3/4"	H-51703	10/60	33	H-51703W	10/60	33
1"	H-51704	6/36	35	H-51704W	6/36	35
1 1/4"	H-51705	6/24	33	H-51705W	6/24	32
1 1/2"	H-51706	2/16	36	H-51706W	2/16	41
2"	H-51707	2/12	38	H-51707W	2/12	38
2 1/2"	H-51708	1/8	54	H-51708W	1/6	39
3"	H-51709	1/3	26	H-51709W	1/4	34
4"	H-51710	1/2	36	H-51710W	1/2	42

CERTIFICATIONS DO NOT APPLY TO 51708, 51709W, 51709, 51709W

w/ 304 Stainless Steel Handle

600 PSI CWP Max/150 WSP						
1/2"	H-51702SSL	10/80	26	H-51702WSSL	10/80	26
3/4"	H-51703SSL	10/60	33	H-51703WSSL	10/60	33
1"	H-51704SSL	6/36	34	H-51704WSSL	6/36	34
1 1/4"	H-51705SSL	6/24	31	H-51705WSSL	6/24	32
1 1/2"	H-51706SSL	2/24	53	H-51706WSSL	2/16	36
2"	H-51707SSL	2/12	38	H-51707WSSL	2/12	38

w/ Wing Style "T" Handle

600 PSI CWP Max/150 WSP						
1/2"	H-51702T	10/80	29	H-51702WT	10/80	27
3/4"	H-51703T	10/60	36	H-51703WT	10/60	34
1"	H-51704T	6/36	37	H-51704WT	6/36	35

w/ 304 Stainless Steel Wing Style "T" Handle

600 PSI CWP Max/150 WSP						
1/2"	H-51702SSW	10/80	42	H-51702WSSW	10/80	42
3/4"	H-51703SSW	10/60	43	H-51703WSSW	10/60	47
1"	H-51704SSW	6/36	42	H-51704WSSW	6/36	47

LEAD-FREE BRASS

Certified to NSF/ANSI 61 NSF/ANSI 61-8



AVAILABLE W/

PRO-CONNECT PP-RCT
EXCLUSIVELY FOR

aquatherm

SEE PAGE 32



AVAILABLE W/

PRO-CONNECT PP-RCT
FOR ANY PP-R OR PP-RCT PIPING SYSTEM

SEE PAGE 33



PRO-CONNECT PRO-PUSH BALL VALVE

Full Port Forged DZR Brass w/ Adjustable Packing Gland - For Connection to Copper, CPVC, or PEX

LEAD-FREE BRASS

Certified to NSF/ANSI 61 & 372 NSF/ANSI 14 ASSE 1061

SIZE	ITEM#	CTN/CASE	CASE WT
Push 200 PSI/200°F Max			
1/2"	H-62702W	10/100	44
3/4"	H-62703W	10/100	63
1"	H-62704W	5/50	56



FULL FLOW FORGED DZR BRASS BALL VALVE

w/ Stainless Steel Wing Style "T" Handle & Adjustable Packing Gland

LEAD-FREE BRASS

Certified to NSF/ANSI 61 & 372 NSF/ANSI 14

SIZE	ITEM#	CTN/CASE	CASE WT
ASTM F1960 PEX 400 PSI CWP Max/250°F Max			
1/2"	H-31702WSSW	10/80	27
3/4"	H-31703WSSW	10/60	30
1"	H-31704WSSW	6/36	33
1 1/4"	H-31705WSSW	5/25	33
1 1/2"	H-31706WSSW	5/25	49
2"	H-31707WSSW	2/12	38
ASTM F1807 PEX 400 PSI CWP Max/250°F Max			
1/2"	H-11702WSSW	10/80	23
3/4"	H-11703WSSW	10/60	26
1"	H-11704WSSW	6/36	26

SEE PAGE 31 FOR A FULL SELECTION OF PEX TRANSITION BALL VALVES



PRO-CONNECT PRESS FULL PORT FORGED BRASS BALL VALVE

w/ Adjustable Packing Gland

STANDARD BRASS

Certified to NSF/ANSI 61

SIZE	ITEM#	CTN/CASE	CASE WT	ITEM#	CTN/CASE	CASE WT
Press 250 PSI CWP MAX/250°F MAX						
1/2"	H-81702	5/50	27	H-81702W	5/50	26
3/4"	H-81703	5/40	33	H-81703W	5/40	32
1"	H-81704	4/20	27	H-81704W	4/20	24
1 1/4"	H-81705	5/20	39	H-81705W	5/20	38
1 1/2"	H-81706	4/16	41	H-81706W	4/16	43
2"	H-81707	2/8	33	H-81707W	2/8	33
2 1/2"	-	-	-	H-81708W	1/1	9
3"	-	-	-	H-81709W	1/1	12
4"	-	-	-	H-81710W	1/1	21

LEAD-FREE BRASS

Certified to NSF/ANSI 61 & 372