

MAGNETIC BOILER FILTER

THE **POWERFUL** WAY
TO STAY **EFFICIENT**

- High-powered 12,000 Gauss magnet captures ferrous debris
- Universal diverter allows use with any piping orientation
- G1 Union connections with or without available isolation valves
- Protects system components
- Maintains system efficiency
- Wide range of G1 Union Accessories offer a solution for most installation needs - see page 19

MAGNETIC BOILER FILTER

12,000 Gauss Magnet, Diverter & G1 Union Connections, Integrated Hose Drain Valve, Air Vent & Filter (Includes Service Tool)

STANDARD BRASS			
SIZE	ITEM#	CTN/CASE	CASE WT
175 PSI CWP Max/250°F Max			
FIP			
3/4"	H-72703	1/4	11
1"	H-72704	1/4	11
MIP			
3/4"	H-74703	1/4	11
1"	H-74704	1/4	11
SWT			
3/4"	H-75703	1/4	11
1"	H-75704	1/4	11
Press			
3/4"	H-78703	1/4	11
1"	H-78704	1/4	11
W/ (2) G1 ISOLATION VALVES			
175 PSI CWP Max/250°F Max			
FIP			
3/4"	H-72713	1/4	11
1"	H-72714	1/4	11
MIP			
3/4"	H-74713	1/4	11
1"	H-74714	1/4	11
SWT			
3/4"	H-75713	1/4	11
1"	H-75714	1/4	11
Press			
3/4"	H-78713	1/4	11
1"	H-78714	1/4	11
BODY ONLY - INSTALL W/ (2) G1 UNION FITTINGS			
G1 Thread			
1"	H-70700	1/4	11

Install on boiler inlet/system return line for maximum boiler protection

