



AQUASORB™

CONCENTRATED FUEL TANK WATER DISPERSANT

DESCRIPTION

AQUASORB™ is a powerful water and sludge dispersant for fuel oil tanks. **AQUASORB™** creates a microscopic dispersion of water that makes it impossible for ice crystals to form and assures the elimination of the water from the tank as it is burned up with the fuel oil. In addition, water based gels or “sludges” are disintegrated and asphaltic sludges are also dispersed.

CHARACTERISTICS

- * Stops ice blockage
- * Helps eliminate sputtering flame and flame failure
- * Helps eliminate slimy or asphaltic sludge
- * Helps prevent leaks due to corrosion

APPLICATIONS

AQUASORB™ is poured directly into the fuel oil tank prior to fuel oil delivery and it will help eliminate service calls due to ice blockage, sputtering flame and flame failure, sludge, corrosion caused leaks, and the need to pump out or dig up buried tanks.

PACKAGING

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
68402	Pint	12	16	0.48
68404	Quart	12	29	1.016

AQUASORB™ CONCENTRATED FUEL TANK WATER DISPERSANT

INSTRUCTIONS

READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

For best results add the appropriate amount of AQUASORB™ as listed below. Pour directly into fuel oil tank prior to fuel oil delivery.

FOR WATER DISPERSION:

Less than 275 gallon tank – 1 pint
275 gallon tank – 1 quart
550 gallon tank – 2 quarts
1080 gallon tank – 1 gallon
2000 gallon tank – 2 gallons

FOR SLUDGE DISPERSION:

1000 gallons of # 2 fuel oil – 1 quart
2000 gallons of # 2 fuel oil – 1 quart
8000 gallons of # 2 fuel oil – 1 gallon

For additional technical information, call Toll Free 1-800-231-3345

PRECAUTIONS

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

**DANGER
HARMFUL OR FATAL IF SWALLOWED
KEEP OUT OF REACH OF CHILDREN
COMBUSTIBLE MIXTURE**

CONTAINS PETROLEUM DISTILLATES.

Avoid contact with hands, face and eyes. Use in well ventilated area. Keep away from heat and open flame. Close container after each use.

FIRST AID: EYES: Flush with plenty of water. **SKIN:** Wash off with soap and water. Seek medical attention if irritation persists. **INGESTION:** If swallowed, DO NOT induce vomiting. Call physician immediately. Keep patient warm and quiet in well ventilated room.

For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS

Wt/Gal @ 77°F	8.0
Flash Point SETA CC	200°F (93°C)
Color	Clear Dark Brown
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY

Rectorseal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Rectorseal® shall not be liable for incidental or consequential damages.

MANUFACTURED IN U.S.A. BY
Rectorseal® • 2601 Spenwick Drive • Houston, Texas 77055-1035
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051
www.rectorseal.com A-02