

# Product Specifications



## 1/2"-13 Drop-In Anchor

**Part number** DA50  
**Category number** 4500  
**UPC** 781002276104

Drop-In Anchors are manufactured with an internally threaded, all-steel exterior shell that features an expansion cone insert used to anchor into the concrete. They are intended to be used in concrete materials only and can be used with any head style screw. The screw can easily be removed, loosened, or re-tightened if needed. Common applications include, pipe hanging, overhead anchoring, hanging strut, sprinkler systems and removable anchoring points.



### Physical Characteristics

<b>Anchor Type</b>	Drop In
<b>Thread Type</b>	UNC
<b>Anchor Diameter</b>	1/2"
<b>Anchor Length</b>	2"
<b>Thread Length</b>	3/4"
<b>Thread Pitch/Thread Per Inch</b>	1/2"-13
<b>Material</b>	Carbon Steel
<b>Finish</b>	Zinc Plated

### Performance Data

<b>Pre-Drill Size</b>	5/8"
<b>Minimum Embedment Depth</b>	2"

#### Applications

Pipe Hanging  
Overhead Anchoring  
Hanging Strut  
Sprinkler Systems and Removable Anchor Points

#### Special Features

Zinc Plated, Easy Bolt Installation/Removal, Lip for Flush Installation, Expansion Cone Insert

<b>Cement Type</b>	Various PSI
--------------------	-------------

### Packaging Details

<b>Standard Qty</b>	50
<b>Master Qty</b>	250
<b>Price Per</b>	100
<b>Package Length</b>	7.20
<b>Package Width</b>	3.40
<b>Package Height</b>	2.20
<b>Net Weight</b>	0.11
<b>Package Weight</b>	5.62

### Certifications

<b>RoHS Compliant</b>	Yes
-----------------------	-----