

# DeWALT®

## ANCHORS & FASTENERS



ICC  
**ESR-3889**  
Cracked & Uncracked  
Concrete

ICC  
**ESR-4042**  
Grout Filled  
CMU



### INTEGRATED WASHER

with serrations under the head secures the attachment



### IDENTIFYING MARK

diameter, length and product marks embossed on head for easy identification

### ENGINEERED STEEL

designed to cut through hard concrete and maintain ductility (bends before breaking)



# DeWALT®

## ANCHORS & FASTENERS

**STANDARD BIT**  
designed for ANSI carbide drill bits

### DUST RELIEF THREAD PROFILE

improves speed & reduces effort for faster installation\*



# FASTENAL®

## Screw-Bolt+™ Concrete Screw Anchor



### Fast Installation\*

Screw-Bolt+™ vs wedge anchor,  
(5/8" diameters)

**22%**  
Faster Installation

DeWALT  
Screw-Bolt+™

Wedge  
Anchor

\*Compared to 5/8" Power-Stud+ SD1 Wedge-Anchor, 5" deep in low strength concrete

	DeWALT Screw-Bolt+™		Hilti® Kwik HUS-EZ*	Simpson® Titen HD*	ITW Red Head® LDT*
ICC Approval	ESR-3889 Cracked & Uncracked Concrete	ESR-4042 Grouted Filled CMU	ESR-3027 Galvanized Not ICC Approved	ESR-2713 Galvanized Not ICC Approved	ESR-3699 5/8" & 3/4" Not ICC Approved
Coating	Zinc & Galvanized		Zinc	Zinc & Galvanized	Zinc & Evirex
ANSI Bit	Yes		Yes	Yes	Undersized Bit
Diameters	1/4 -3/4"		1/4"-3/4"	1/4"-3/4"	3/8"-3/4"
Matched Tool	DeWALT		Hilti Tools	No	No

\*Hilti and Kwik HUS-EZ are registered trademarks of Hilti Corporation  
\*Simpson and Titen HD are registered trademarks of Simpson Strong-Tie Company, Inc.  
\*ITW and Redhead are registered trademarks of Illinois Tool Works, Inc.

# DEWALT®

## ANCHORS & FASTENERS



ZINC PLATED SCREW-BOLT+™



GALVANIZED SCREW-BOLT+™

- Designed for standard ANSI tolerance drill bits
- Patented thread design offers low installation torque
- Tough threads for tapping high strength concrete
- Ratchet teeth on underside of hex washer head lock against the fixture
- Can be installed closer to the edge than traditional expansion anchors
- Fully removeable and reinstallable in same hole
- Fast installation with powered impact wrench
- Diameter, length and identifying marking stamped on head of each anchor
- One-piece, finished head design

### Approvals & Listings

International Code Council, Evaluation Service (ICC-ES), ESR-3889 for Concrete. Approved for seismic loading.

International Code Council, Evaluation Service (ICC-ES), ESR-4042 for Masonry. Approved for seismic loading.

Code compliant with the 2015 IBC, 2015 IRC, 2012 IBC, 2012 IRC, 2009 IBC, 2009 IRC, 2006 IBC and 2006 IRC



ESR-3889  
Cracked & Uncracked  
Concrete



ESR-4042  
Grout Filled  
CMU



# FASTENAL®

## Screw-Bolt+™ Concrete Screw Anchor

CATALOG NUMBER				ANCHOR	QTY	MASTER QTY
ZINC PLATED	FASTENAL#	GALVANIZED	FASTENAL#			
*PFM1411000	FASTENAL#	-		1/4" x 1-1/4"	100	600
PFM1411020	FASTENAL#	-		1/4" x 1-3/4"	100	600
PFM1411060	FASTENAL#	-		1/4" x 2-1/4"	100	600
PFM1411080	FASTENAL#	-		1/4" x 2-5/8"	100	500
PFM1411100	FASTENAL#	-		1/4" x 3"	100	500
*PFM1411160	FASTENAL#	-		3/8" x 1-3/4"	50	300
PFM1411220	FASTENAL#	-		3/8" x 2-1/2"	50	300
PFM1411240	FASTENAL#	PFM1461240	FASTENAL#	3/8" x 3"	50	250
PFM1411280	FASTENAL#	PFM1461280	FASTENAL#	3/8" x 4"	50	250
PFM1411300	FASTENAL#	PFM1461300	FASTENAL#	3/8" x 5"	50	250
PFM1411320	FASTENAL#	PFM1461320	FASTENAL#	3/8" x 6"	50	150
*PFM1411340	FASTENAL#	-		1/2" x 2"	50	200
PFM1411360	FASTENAL#	-		1/2" x 2-1/2"	50	200
PFM1411380	FASTENAL#	-		1/2" x 3"	50	150
PFM1411420	FASTENAL#	PFM1461420	FASTENAL#	1/2" x 4"	50	150
PFM1411460	FASTENAL#	PFM1461460	FASTENAL#	1/2" x 5"	25	100
PFM1411480	FASTENAL#	PFM1461480	FASTENAL#	1/2" x 6"	25	75
PFM1411520	FASTENAL#	PFM1461520	FASTENAL#	1/2" x 8"	25	100
*PFM1411540	FASTENAL#	-		5/8" x 3"	25	100
PFM1411580	FASTENAL#	-		5/8" x 4"	25	100
PFM1411600	FASTENAL#	PFM1461600	FASTENAL#	5/8" x 5"	25	75
PFM1411640	FASTENAL#	PFM1461640	FASTENAL#	5/8" x 6"	25	75
PFM1411680	FASTENAL#	PFM1461680	FASTENAL#	5/8" x 8"	25	50
*PFM1411700	FASTENAL#	-		3/4" x 3"	20	60
PFM1411720	FASTENAL#	-		3/4" x 4"	20	60
PFM1411760	FASTENAL#	-		3/4" x 5"	20	60
PFM1411800	FASTENAL#	PFM1461800	FASTENAL#	3/4" x 6"	20	60
PFM1411840	FASTENAL#	PFM1461850	FASTENAL#	3/4" x 8"	10	40
PFM1411880	FASTENAL#	-		3/4" x 10"	10	20

\*denotes sizes which are less than the minimum standard anchor length for Strength Design. The published size length of the anchor is measured from under the head.

Dealer Stamp

# 1-800-4 DEWALT®

## www.DEWALT.com