# **GOULOFF-JORDAN** SURVEYING AND DESIGN, INC.

BOUNDARY RETRACEMENT SURVEY Lot 23, 24, 25, 26, 29, 30 and 31 Replat of Lake Shore Addition to Bear Lake

SHEET 1 OF 2

1133 BROADWAY FORT WAYNE, IN 46802 PH (260) 424-5362 FAX (260) 424-4916

4587 West "A" Drive, Albion, IN 46701 S. Lakeshore Drive (E)LEGEND Date: May 13, 2016 For the exclusive use of: Flood Note:

By graphic plotting only and subject to map scale uncertainties, the real estate described and depicted hereon appears to lie in Zone "X" (NOT considered a special flood hazard area) on FIRM Map Number 18113C0285 D, dated March 2, 2015 for Noble County, Indiana. Job No.: 20160113  $\omega$ (E) AKE EAR 43.2' (p) CALCULATED RECORDED MEASURED PLATTED INFORMATION 53.6.10) 1/2" Rebar Fnd. (0.0) One Story Framed Residence Lot 27 7.76.9A. (M) 1.76.5. (6) 80' (p) <1/2" Rebar Fnd. (0.0) 159.64  $\tilde{\varepsilon}$ 121.00' (p & m) 80' (p) Taylor 160' (p) 1/2" Rebar Fnd. (0.0) Lot 26 Lot 80' (p) 80' (p) Shed 8 3/8" Rebar Fnd. (0.0) 34 80.19' (m) 80' (p) 90°10' (m) 80' (p) 3/8" Rebar -Fnd. (0.0) 25' West "B" Drive 30' Right-of-Way (p) West "A" Drive Lot 29 Lot 25 80' (p) 17.3 Shed 80' (p) 239.60' (m) 80' (p) 80' (p) 276.20' (p & m) 240.00' (p & m) Lot 24 240 Lot 30 # 4587 80' (p) 80 છે ন্ত 26' 30' Right-of-Way (p) Total Area: 1.03 Ac.  $\triangleright$ SCALE:1"=60' 46' Lot 23 80' (p) Lot 31 80 12' x 12' Shed Scale in feet છે +/- (m) 72.7' 5/8" Rebar Fnd. (0.0) 80' (p) 79.89' (m) 80' (p) 80.15' (m) 120 160.00 (p & m) -1/2" Rebar Fnd. (0.0) Replat of Lake Shore Addition to Bear Lake Plat Bk. 2, pg. 58 - 5/8" Rebar Fnd. (+0.1) 80.07' (m) 79.94' (m) Lot 22 Lot 32 80' (p) g 5/8" Rebar Fnd. (0.0) 80' (p) 80' (p) 80' (p) 79.79' (m)



## SURVEYOR'S REPORT

Lot 23, 24, 25, 26, 29, 30 and 31 Replat of Lake Shore Addition to Bear Lake 4587 West "A" Drive, Albion, IN 46701

LEGAL DESCRIPTION - D.R. 145, pg. 500, D.R. 200, pg. 495, Doc. # 981000100 and D.R. 180, pg. 189

Lots 23, 24, 25, 26, 29, 30 and 31 in Replat of Lake Shore Addition to Bear Lake, according to the plat thereof recorded in Plat Book 2, page 58 in the Office of the Recorder of Noble County, Indiana.

#### SURVEYOR'S REPORT

This report and the accompanying survey plat have been prepared in accordance with Title 865, Article 1, Rule 12, Sec 1-29 and all amendments thereto of the Indiana Administrative Code, which establishes the minimum standards for the practice of land surveying.

Monuments set are 5/8 inch round by 24 inch long steel rebars with yellow plastic caps stamped "GOU LS29500017", and set flush with the ground surface.

Monuments found are noted with an above (x,x) or below (-x,x) ground surface dimension.

This purpose for this survey is to "retrace" the boundary of the real estate described hereon.

#### THEORY OF LOCATION:

The lines and corners for this survey were established as depicted on the survey drawing and per information shown on the plat of Replat of Lake Shore Addition to Bear Lake.

The uncertainty in the lines and corners found or established by this survey are as follows:

- (A) Availability and condition of reference monuments:

  Monuments found are described and depicted on the survey drawing.

  Uncertainty created by the location of the monuments found or set on the subject property due to variations in reference monuments (monuments found on the subject property and on adjacent properties) is the difference between
  - monuments (monuments found on the subject property and on adjacent properties) is the difference between "measured" and "platted" or "recorded" angular or distance measurements as depicted on the survey drawing.

    The maximum uncertainty for this survey is 0.44 feet.
- (B) Occupation or possession lines:

  No uncertainty was created by visible occupation or possession lines.
- (C) Clarity or ambiguity of the record description and or adjoiner's descriptions: No uncertainty was created by the above mentioned documents.
- (D) This survey falls under the classification of a "Suburban" survey. The acceptable relative positional precision (random errors in measurements) = 0.13 feet (40 millimeters) plus 100 parts per million as specified in Section 7 of said Rule 12.

### SURVEYOR'S CERTIFICATION

This survey was performed by, or under the responsible direction of the undersigned registered land surveyor and to the best of said registered land surveyor's knowledge and belief, said survey was executed according to the applicable survey requirements of 865 IAC-1-12-1 thru 29.

Field work for this survey was performed on May 10, 2016.

DATED THIS 13th DAY OF MAY, 2016.

Timothy C. Gouloff, R.L.S. 29500017

Job No.: 20160113