

Meteor Loader Mount

The loader mount Meteor is the ideal snow blower package for owners of small tractors equipped with loader arms. The package includes a self contained PTO driven power pack to drive the hydraulics required by the snow blower.

The power pack holds up to 30 gallons and runs 2500 PSI at 30 gallons per minute. Minimum horse power requirement is 40.

Models	SBLM66	SBLM76	SBLM86
Recommended HP	40-60HP	40-60HP	40-60HP
Max. Operating Weight	8,000 LBS.	8,000 LBS.	8,000 LBS.
Cutting Width	66"	76"	86"
Cutting Edge	3/8" x 3"	3/8" x 3"	3/8" x 3"
Skid Shoes	3/8" x 1-1/2"	3/8" x 1-1/2"	3/8" x 1-1/2"
Auger Tube	3-1/2" OD	3-1/2" OD	3-1/2" OD
Auger Flighting	5/16 x 2-1/4	5/16 x 2-1/4	5/16 x 2-1/4
Auger Diameter	19"	19"	19"
Roller Chain	#60	#60	#60
Hitch Plate	Quick-tach	Quick-tach	Quick-tach
Chute Rotation	Hydraulic	Hydraulic	Hydraulic
Chute Diameter	12"	12"	12"
Main Body Height	31"	31"	31"
Chute Deflector	Hydraulic	Hydraulic	Hydraulic
Fan Diameter	26"	26"	26"
Fan Depth	8"	8"	8"
Auger Drive	Hydraulic	Hydraulic	Hydraulic
Fan Drive	Hydraulic	Hydraulic	Hydraulic

https://mkmartin.ca/print.php 1/3

Weight (LBS.) *	970	1,015	1,065
-----------------	-----	-------	-------

^{*} Weight includes snowblower only.

Features

High Tensile Steel Ribbon Flighting

To deliver even the heaviest wet snow to the awaiting fan, Meteor Snow Blowers use machine formed hand welded augers made with high tensile steel ribbon flighting to provide strength and durability for years to come.

Five Blade Fan

All Meteor Snow Blowers now feature a standard 5 blade fan. The five blades not only evacuate high volumes of snow quickly, but also feature tighter tolerance to the housing increasing velocity of the snow exiting the chute.

Manual Deflector

All Meteor Snow Blowers come with a manual pin style deflector allowing a true set it and forget approach to blowing snow.

Skid Shoes

Meteor Snow Blowers come equipped with adjustable skid shoes extending the life of the cutting edge and helping to protect surfaces from damage commonly associated with snow removal.

Manual Rotator

Manual rotators are standard on SB48, SB54, and SB60 single auger models and can be optionally outfitted on most models where operators can safely reach the adjustment handle.

Hydraulic Rotator

The optional hydraulic rotator is the ideal upgrade for tractors with cabs or for contractors/property managers needing to make frequent adjustments.

Hydraulic rotators are standard equipment on SB97D, SB108D, and SB120D models.

Electric Rotator

When hydraulic power isn't available the 12V electric rotator provides a hands off approach to chute rotation. Contact MK Martin for compatibility and availability.

Hydraulic Deflector

Hydraulic deflectors control the distance and arc of the thrown snow and are an available option on all models.

Multi-Hinged Deflector

The optional multi-hinged deflector is available for most models and allows increased precision in where snow is blown allowing snow to be placed closer to the blower or into a truck to be hauled away.

1000 RPM PTO Kit

Available for the SB97D, SB108D, and the SB120D models, this kit allows the PTO of larger tractors to run at 1000 RPM without damaging the standard 540 RPM gearbox. The 1000 RPM Kit also raises the input shaft to allow the PTO shaft to run at a lesser angle on larger tractors increasing the efficiency and life of the driveline components.

Note: features rotation reversal for front mount applications if required.

https://mkmartin.ca/print.php 2/3

https://mkmartin.ca/products/loader.php 1.855.664.2752

https://mkmartin.ca/print.php 3/3