alula™
Simplifying · Security

BAT-Connect

Alula's new **BAT-Connect** is the ultimate system takeover device, easily upgrading legacy security platforms to a modern, mobile experience. Much more than a basic communicator, this intuitive device smartly bridges intrusion security, video and automation with the Alula iOS or Android Apps. Fueled by the encrypted, lightning-fast Alula network, system control is delivered instantly to the smart devices your customers already use and love.

Armed with the BAT-Connect, security dealers can streamline their takeover business, cut install time and simplify operations. The easy-to-install communicator is broadly compatible with common panels, giving security dealers a game changer upgrade for 15-Million security systems online today.

- INSTANTLY MODERNIZE MOST LEGACY SECURITY SYSTEMS WITH MOBILE CONTROL
- OFFER NEW SERVICE UPGRADES BEYOND BASIC INTRUSION SECURITY
- VIDEO READY, ENABLED THROUGH THE ALULA MOBILE APP
- HOME AUTOMATION READY, LINK TO ANY Z-WAVE DEVICE
- SUNSET-PROOF COMMUNICATOR, WITH ETHERNET AND WIFI ON BOARD
- TRIPLE-PATH CONNECTIVITY GIVES INSTALL FLEXIBILITY AND AUTO-SWITCHING TO ALWAYS MAINTAIN ALARM REPORTING
- CAT-M1 IOT OPTIMIZED! 5G READY KEEPS YOU AHEAD OF TECH CHANGES, 4G LTE LINKS TO CURRENT CELL STANDARD
- NEAR UNIVERSAL PANEL COMPATIBILITY
- KEYSWITCH ARMING FOR REMOTE INTERACTIVE CONTROLS
- AUTO-BUS CONNECTION SAVES SETUP TIME, INSTANTLY JOINING EXISTING PANELS



CELLULAR · Z-WAVE PLUS · 5G · 4G LTE · WIFI · ETHERNET

Compatible with 4G LTE and planned 5G network specifications.

ALULA

Download on the App Store · GET IT ON Google Play

2340 Energy Park Drive, Suite #100, St. Paul, MN 55108 • 1-888-88-ALULA • WWW.ALULA.NET

TECHNICAL SPECIFICATIONS

	RE930XP
Physical	
Housing Dimensions	8.5 x 5.0 x 1.3 in
Weight	10 oz (284 g)
Tamper Activations	Cover Opening, Wall Removal
Mounting Fasteners	#4 or #6 screws (not included)
Environmental	
Operating Temperature	32°F to 120°F (0°C to 49°C)
Storage Temperature	-4°F to 86°F (-20°C to 30°C), Long Term
Maximum Humidity	85% non-condensing relative humidity
Communication Paths	
LTE Category M1 Wi-Fi Ethernet	
Certification	
Certification Listings	RE930XP: FCC, IC, Verizon, AT&T

Specifications subject to change without notice.