

*** Try these other fine ELK products ***

M1 Cross Platform Control

- M1 (Std)** Integrates Security, Lighting, Telephone, and Energy Management. Powerful "Rules" based automation capabilities. Up to 208 Zones.
- M1G (Gold)** More powerful version of M1 with more expansion and capabilities.
- M1KP** LCD Keypad, 2 x 16 Character, backlit
- M1XIN** 16 Zone (input) expander. Up to 12 per sys.
- M1XOVR** 16 Output expander. 8 voltage/8 Relays
- M1XOV** 16 Output expander. All low voltage pins
- M1RB** 8 relay board for use w/Ctrl,XOVR, or XO
- M1DBH** Data Bus wiring hub for multiple homeruns
- M1XEP** Ethernet port expander/interface
- M1XSP** Serial port expander for additional serial ports.

Magic Module Series

- MM220** Magic Module, 2 Input, 2 Output, Programmable
- MM443** Magic Module, 4 Input, 4 Output, Programmable
- MM447** Automation Controller w/Voice,Caddx Interface
- MV480** Recordable Voice Module, 400 Channels
- MK400** Starter Kit, Includes MM443 & MK485
- MK485** Programming Kit, MB485, Cables, Software
- MB485** Data Bus Interface, RS232 to RS485

Rust Free Sirens / Speakers

- 1RT** Speaker & Stainless Steel Enclosure
- 150RT** Siren & Stainless Steel Enclosure

Speakers & Sirens

- 44** Speaker, 30 W,8 Ohm Compact Horn
- 45** Siren, Compact Horn, 118db
- M120** Siren, Single Tone, 107db, Mini Horn
- SP15** Speaker, 15 watt, Small Horn
- SP30** Speaker, 30 watt, Horn
- SP35** Speaker, 20 watt, Interior
- SP40** Speaker, 40 watt, Horn
- SS15** Siren, Dual Tone, 110db, Horn
- SS30** Siren, Dual Tone, 120db, Horn
- SS36** Siren, Dual Tone, 105db, Interior

ECHO™ Sirens & Speakers

- 73** ECHO Speaker, 20 Watt, Interior
- 74** ECHO Dual Tone Siren, Interior
- 75** ECHO Voice Siren, Interior
- 870** ECHO Speaker, Self Amplified

Siren & Voice Drivers

- 100** High Performance Siren Driver
- 110** Voice Siren Driver, English & Spanish
- 120** Recordable Voice Module and Siren
- 124** Recordable Voice Module, 4 Channels

Surge Suppressors

- 950** Surge Suppressor, Phone & Power Line
- 951** Surge Suppressor, Phone - Single Line
- 955** Surge Suppressor, Phone - Dual Line

Relay Modules

- 912** Compact Relay,12 Vdc, SPDT
- 912B** Heavy Duty Compact Relay,12/24 Vdc, SPDT
- 924** Sensitive Relay, 12/24 Vdc, DPDT
- 941** Alarm Output Director
- 960** Delay Timer Relay, 1 sec. to 60 min.

Power Products

- 1250** Battery, Lead Acid, 12v, 5Ah
- 1280** Battery, Lead Acid, 12v, 8Ah
- P112** 12 Volts DC, 1 Amp Power Supply w/Enclosure
- P124** 24 Volts DC, 800mA Power Supply w/Enclosure
- P1216** 12 Volts DC, 1.5 Amp Power Supply
- P412** 12 Volts DC, 4 Amp Power Supply
- P624** Power Supply & Battery Charger
- PD9** Power Distribution Module
- 965** Low Battery Cutoff and Power Switch
- TRG1640** Transformer, 16.5VAC @ 40 VA
- TRG2440** Transformer, 24VAC @ 40 VA

Accessories

- 129** Computer Sound Card Interface
- 800** Audio Amplifier, 10 Watts
- 900-2** "B" Connectors,Unfilled,500 pcs
- 902-2** "B" Connectors,Gel filled,500 pcs
- 980** Telephone Line Fault Monitor
- 999** Double Sided Tape
- SL1** Strobe Light, 4 colors available
- WK1** Wall Mount Kit for SL1 Strobes

For more information contact your local Distributor or:
 ELK PRODUCTS,INC 828-397-4200 FAX 828-397-4415
<http://www.elkproducts.com> Email: info@elkproducts.com

Two Way Microphone ELK-M1TWM

APPLICATION:

The **ELK-M1TWM** microphone connects to the ELK-TWI two way listen-in interface. Up to 12 microphones total may be connected.



Two Way Microphone ELK-M1TWM



FEATURES:

- Simple two wire connection
- High Sensitivity
- Up to 12 may be connected to one M1TWI

SPECIFICATIONS:

- Operating Voltage: Powered from M1TWI
- Current Draw. 5mA each
- Circuit Board Dimensions: 1.5" x 1"



828-397-4200 Voice
 828-397-4415 Fax
<http://www.elkproducts.com>
 email: info@elkproducts.com
 PO Box 100 • Hwy. 70W • Hildebran, NC 28637 • USA

Instructions Printed On Inside