

Product Specifications



Flip Toggle Kit 1/4" W/Screws (25 pack)

Part number FTG14B25
Category number 4740
UPC 781002857594

The Flip Toggle Anchor is a single piece, nylon body anchor with a metal tilting head ideal for use in drywall, plaster and hollow wall concrete blocks. It's unique tilting mechanism ensures a trouble-free installation that yields twice the strength of a regular toggle bolt of the same bolt diameter.



Physical Characteristics

Anchor Type	Flip Toggle
Head Type	Pan
Screw Size	1/4"-20 x 2-1/2"
Anchor Diameter	1/4"
Thread Pitch/Thread Per Inch	1/4"-20
Number of Pieces	25

Packaging Details

Kit Contains (25) Flip Toggle Anchors, (25) 1/4"-20 x 2-1/2" Pan Phillips/Slotted Machine Screw	
Standard Qty	1
Master Qty	5
Price Per	1
Package Length	2.38
Package Width	6.13
Package Height	10.75
Net Weight	1.64
Package Weight	1.64

Performance Data

Safe Tension Load 1/2" Drywall: 74lbs, 5/8" Drywall: 120lbs, Hollow Concrete Block: 535lb	
Shear Strength 1/2" Drywall: 274lbs, 5/8" Drywall: 418lbs, Hollow Concrete Block: 870lbs	
Safe Shear Load 1/2" Drywall: 137lbs, 5/8" Drywall: 209lbs, Hollow Concrete Block: 600lb	
Grip Range	1/2" to 2-1/8"
Hole Diameter	1/2"
Applications Drywall Hollow Block Walls and Ceilings	
Special Features Twice as Strong as Toggle Bolt, Fast and Easy Installation, Suitable for Overhead Applications, One Strap Design, Only Requires 1/2" Hole, Used with Any Bolt Length up to 3-3/4"	

Certifications

RoHS Compliant	Yes
----------------	-----