



333 Bayview Avenue
Amityville, New York 11701
For Sales and Repairs, (800) 645-9445
For Technical Service, (800) 645-9440 or visit us at
<http://tech.napcosecurity.com/>
(Note: Technical Service is for security professionals only)
Publicly traded on NASDAQ Symbol: NSSC
© NAPCO 2016

GEMC-PS24V4A-R 4 AMP SUPERVISED POWER SUPPLY / CHARGER DATA SHEET

WI1893A 01/16

DESCRIPTION

The GEMC-PS24V4A-R is both a charger and a supervised power supply rated at 24VDC/4A. Input rating is 120VAC, 60Hz, 3A. Fuse rated 5A, 250V. Replace only with UL Listed fuse rated 5A, 250V (see WI1653).



FEATURES

- 24VDC output.
- Maximum charge current 1.96A.
- 4 ampere continuous supply current at 24VDC.
- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.

- AC input, DC output.
- Short circuit and thermal overload protection. Specified at 25° C ambient.

PHYSICAL

Board Dimensions: 9"(L) x 6"(W) x 1 $\frac{5}{8}$ "(H)

AGENCY LISTINGS

UL864 9th Edition: Commercial Fire
UL985 Household Fire Warning System Units
NFPA 72 National Fire Alarm Code
CSFM: California State Fire Marshall
NYCFD: NYC Fire Department

ORDERING INFORMATION

GEMC-PS24V4A-R: 4A, 24V Power Supply



333 Bayview Avenue
Amityville, New York 11701
For Sales and Repairs, (800) 645-9445
For Technical Service, (800) 645-9440 or visit us at
<http://tech.napcosecurity.com/>
(Note: Technical Service is for security professionals only)
Publicly traded on NASDAQ Symbol: NSSC
© NAPCO 2016

GEMC-PS24V4A-R 4 AMP SUPERVISED POWER SUPPLY / CHARGER DATA SHEET

WI1893A 01/16

DESCRIPTION

The GEMC-PS24V4A-R is both a charger and a supervised power supply rated at 24VDC/4A. Input rating is 120VAC, 60Hz, 3A. Fuse rated 5A, 250V. Replace only with UL Listed fuse rated 5A, 250V (see WI1653).



FEATURES

- 24VDC output.
- Maximum charge current 1.96A.
- 4 ampere continuous supply current at 24VDC.
- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.

- AC input, DC output.
- Short circuit and thermal overload protection. Specified at 25° C ambient.

PHYSICAL

Board Dimensions: 9"(L) x 6"(W) x 1 $\frac{5}{8}$ "(H)

AGENCY LISTINGS

UL864 9th Edition: Commercial Fire
UL985 Household Fire Warning System Units
NFPA 72 National Fire Alarm Code
CSFM: California State Fire Marshall
NYCFD: NYC Fire Department

ORDERING INFORMATION

GEMC-PS24V4A-R: 4A, 24V Power Supply