



PRODUCT DATA SHEET

Part Number: 16/2FPLR-WT

Description: 2C/16 AWG SOLID FPLR PVC- WHITE- 1000 FT SPOOL

Suitable Application: Rated Fire Alarm Cable

Construction Details:

Total Number Conductors	2
Awg	16
Stranding	Solid
Conductor Material	Bare Copper
Insulation Material	Polyvinylchloride
Insulation Thickness	.010"
Nominal Insulation Diameter	.071"
Color Code	Black/Red
Cabling Overall Lay	2 1/2" left hand lay
Nominal Cabling Diameter	.142"
Final Jacket Material	Sunlight Resistant Polyvinylchloride
Nominal Thickness	.015"
Jacket Color	Red
Nominal Jacket Diameter	.172"
Ripcord	Yes

Print (Surface)

Inkjet	Yes
Sequential Foot Marks	Yes

Print Legend:

16 AWG 2C RISER FIRE ALARM CABLE (ETL)us TYPE FPLR OR CMR OR CL2R 3054355

Electricals

Voltage Rating:	300V
Conductors:	ASTM B-3, B-8
Temperature Rating:	-20C to +75C

Applicable Standards:

ETL Type	FPLR,CMR, and CL2R
ROHS Compliant	Yes

Modified: Simon

Approved: Andrew

Rev Date: 04/2013