

SPECIFICATION SHEET

www.scp5e.com
sales@scp5e.com

14-May-2014

Product Number : **16/2SP-26-BL**

RoHS

Description : **2C/16 AWG 26 STRAND SPEAKER CABLE- BLUE- 500 FT BOX**

Conductor :	16 AWG 26 Strand SBC Cond.		
Total Cable Weight :	47 kg/km	Final Diameter :	0.196 inches
Insulation :	PVC	Jacket :	PVC
DC Resistance 25°C:	4.3 Ohms / 1000 ft	Mutual Capacitance :	22.2 pF/ft
Impedance :	77 Ohms		
Velocity of Prop :	70 %	Inductance. :	3.9 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 16/2SP-26 - - - 2/C 16 AWG AWG
26 STRAND TYPE CMR/CL3R FT4 - - (UL) OR C(UL) E198137 CE EU ROHS
EC P§-L§ ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.109
Ins Thickness: 0.010
Jkt Thickness: 0.019
Certified: UL CMR/CL3R
Flame Rating: Riser
Max Voltage: 300V

UL Standards: 13 & 444
NEC Articles: 725
Min. Bend Radius/Minor Axis: 1.372
Operating Temperature: -20°C to 60°
C Standard UL Temp: 60°C

Packaging Weight: 15 lbs / 6.82 kgs

(All of the above values are approximated to within +/- 10%)