



Structured Cable Products

Quality Installations Deserve Quality Products

SPECIFICATION SHEET

Phone: 866-470-5742

www.scpcat5e.com

30-May-2014

Product Number : **16/2-GY**

RoHS

Unsh Riser 1/PR 16/26 AWG SBC

PVC Insulation

Gray PVC Riser Jacket

1000 FEET Reelex

Conductor : 16 AWG 26 Strand SBC Cond.

Total Cable Weight : 43 kg/km

Final Diameter : 0.200 inches

Insulation : PVC

Jacket : PVC

DC Resistance 25°C: 4.3 Ohms / 1000 ft

Mutual Capacitance : 20.1 pF /ft

Impedance : 84.7 Ohms

Velocity of Prop : 63 %

Inductance. : 1.4 mH /km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 16/2 --- (UL) CL3R E198137 (UL)
C(UL) CMR UNSH 1/PR 16 AWG --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7
8 9 RoHS

Cabled OD Avg: 0.134

Ins Thickness: 0.011

Jkt Thickness: 0.018

Certified: UL CL3R / UL C(UL) CMR

Flame Rating: Riser

Max Voltage: 300V

(All of the above values are approximated to within +/- 10%)

3071651.10R.1000