



Structured Cable Products

Quality Installations Deserve Quality Products

SPECIFICATION SHEET

www.scpca5e.com
sales@scpcat5e.com

12-Mar-2014

Product Number : **18/2FPLR**

RoHS

Description : **2C/18 AWG SOLID FPLR PVC- RED- 1000 FT SPOOL**

Conductor :	10 AWG Solid HBC Cond.		
Total Cable Weight :	29 kg/km	Final Diameter :	0.151 inches
Insulation :	PVC	Jacket :	PVC
DC Resistance 25°C:	6.6 Ohms / 1000 ft	Mutual Capacitance :	19.6 pF/ft
Impedance :	79.7 Ohms		
Velocity of Prop :	66 %	Inductance. :	1.4 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 18/2FPLR - - - RISER FIRE
ALARM CABLE (UL) CL2R/CL3R E132885 OR FPLR (UL) C(UL) CMG CMR
UNSH 2/C 18 AWG SOLID PVC JKT --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6
7 8 9 RoHS

Cabled OD Avg: 0.104	NEC Articles: 800, 760, 725
Ins Thickness: 0.010	Min. Bend Radius/Minor Axis: 1.057 inches
Jkt Thickness: 0.015	Operating Temperature : -20°C to 60°C
Certified: UL CL2R/CL3R OR FPLR/CMG/CMR	Standard UL Temp : 60°C
Flame Rating: Riser	
Max Voltage: 300V	

Package Weight: 16 lbs / 7.27 kgs

(All of the above values are approximated to within +/- 10%)

2981802.03S.1000