



SPECIFICATION SHEET

www.scpcat5e.com
sales@scpcat5e.com

15-May-2014

Product Number : 22/4SOL-COIL-BL

RoHS

Description : 4C/22 AWG SOLID COPPER PVC COIL PACK- BLUE- 500 FT

Conductor : 10 AWG Solid HBC Cond.	
Total Cable Weight : 18 kg/km	Final Diameter : 0.120 inches
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 19.5 Ohms / 1000 ft	Mutual Capacitance : 21.9 pF/ft
Impedance : 80.8 Ohms	
Velocity of Prop : 68 %	Inductance. : 1.3 mH/km
Print Notes : Sequentially marked per 2FT (0 - infinity)	
Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 22/4SOL - - - (UL) CL3R E198137 (UL) C(UL) CMR UNSH 4/C 22 AWG - - - ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS	
Cabled OD Avg: 0.082 Ins Thickness: 0.006 Jkt Thickness: 0.015 Certified: UL CL3R/CMR Flame Rating: Riser Max Voltage: 300V	NEC Articles: 800, 725 Min. Bend Radius/Minor Axis: .84 inches Operating Temperature : -20°C to 60°C Standard UL Temp : 60°C

Package Weight: 6 lbs / 2.73 kgs

(All of the above values are approximated to within +/- 10%)