	CPG1.5/3	CPG1.5/4	CPG2.5/3	CPG2.5/4
				
	3 Connection Ground Terminal 2 Jumper Channels	4 Connection Ground Terminal 2 Jumper Channels	3 Connection Ground Terminal 2 Jumper Channels	4 Connection Ground Terminal 2 Jumper Channels

Dimensions & Weight

Width / Length	**3.5 mm** / 54.5 mm	**3.5 mm** / 63.5 mm	**5 mm** / 62.5 mm	**5 mm** / 73.0 mm
Height w DIN Rail 35 x 7.5 mm 35 x 15 mm	32.8 mm 40.3 mm	32.8 mm 40.3 mm	38.3 mm 45.8 mm	38.3 mm 45.8 mm
Weight per piece	5.8 g	6.4 g	8.2 g	10.2 g

Technical Data/Ratings

Approvals	E220514	60947-7-1	E220514	60947-7-1	E220514	60947-7-1	E220514	60947-7-1
Wire Size (solid / stranded)	**24-14 AWG**	0.2-1.5 mm²	**24-14 AWG**	0.2-1.5 mm²	**24-12 AWG**	0.2-2.5 mm²	**24-12 AWG**	0.2-2.5 mm²
Voltage Rating	600 V	1000V AC/DC	600 V	1000V AC/DC	600 V	1000V AC/DC	600 V	1000V AC/DC
Current Rating	–	–	–	–	–	–	–	–
Insulation Material	Polyamide 66		Polyamide 66		Polyamide 66		Polyamide 66	

Installation Instructions

Wire Stripping Length	8 mm	8 mm	10 mm	10 mm
Screwdriver	SCM0.4/2.5 (0.4 x 2.5 mm blade)	SCM0.4/2.5 (0.4 x 2.5 mm blade)	SCM0.5/3.0 (0.5 x 3.0 mm blade)	SCM0.5/3.0 (0.5 x 3.0 mm blade)

Terminal Blocks

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Ground/ Earth Yellow / Green	**CPG1.5/3**	100	**CPG1.5/4**	100	**CPG2.5/3**	100	**CPG2.5/4**	100

Jumpers

		Cat. No.	Imax	Std. Pk.	Cat. No.	Imax	Std. Pk.	Cat. No.	Imax	Std. Pk.	Cat. No.	Imax	Std. Pk.
Shorting Link/ Jumpers	2 pole	JX1.5/2	16A	100	JX1.5/2	16A	100	JX2.5/2	24A	100	JX2.5/2	24A	100
	3 pole	JX1.5/3	16A	50	JX1.5/3	16A	50	JX2.5/3	24A	50	JX2.5/3	24A	50
	4 pole	JX1.5/4	16A	50	JX1.5/4	16A	50	JX2.5/4	24A	50	JX2.5/4	24A	50
	5 pole	–	–	–	–	–	–	JX2.5/5	24A	50	JX2.5/5	24A	50
	6 pole	–	–	–	–	–	–	JX2.5/6	24A	10	JX2.5/6	24A	10
	7 pole	–	–	–	–	–	–	JX2.5/7	24A	10	JX2.5/7	24A	10
	8 pole	–	–	–	–	–	–	JX2.5/8	24A	10	JX2.5/8	24A	10
	10 pole	JX1.5/10	16A	10	JX1.5/10	16A	10	JX2.5/10	24A	10	JX2.5/10	24A	10
	16 pole	–	–	–	–	–	–	–	–	–	–	–	–
Step Down Jumpers	4-2.5 mm²	–	–	–	–	–	–	JXS4/2.5	32A	50	JXS4/2.5	32A	50
	6-2.5 mm²	–	–	–	–	–	–	JXS6/2.5	41A	50	JXS6/2.5	41A	50
	6-4 mm²	–	–	–	–	–	–	–	–	–	–	–	–

Accessories

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
End Plate	EPCP1.5/3	50	EPCP1.5/4	50	EPCX2.5/3	50	EPCX2.5/4	50
Partition Plate	PPCX4/3	50	PPCX4/4	50	PPCX4/3	50	PPCX4/4	50
DIN Rail	2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20
End Stop	CA103 / CA104	50	CA103 / CA104	50	CA103 / CA104	50	CA103 / CA104	50
Test Plug	–	–	–	–	TX2.5	20	TX2.5	20
Marking Tag	MS3.5	1 Pk. (100 tags)	MS3.5	1 Pk. (100 tags)	MT5	1 Pk. (100 tags)	MT5	1 Pk. (100 tags)