

CM1.5S



CM1.5S2



CM2.5S



CM2.5S2



Dimensions

Width	5 mm	8 mm	6 mm	6 mm
Length	26.5 mm	26.5 mm	30 mm	30 mm
Height (Panel Mount)	18.0 mm	18.0 mm	20.0 mm	20.0 mm

Technical Data/Ratings

Approvals	CE, UL, IEC, RoHS	UL, IEC, RoHS	UL, IEC, RoHS	UL, IEC, RoHS	UL, IEC, RoHS	UL, IEC, RoHS	UL, IEC, RoHS
Wire Size (solid / stranded)	24-16 AWG, 0.2-1.5 mm ²	24-16 AWG, 0.2-1.5 mm ²	22-12 AWG, 0.2-2.5 mm ²	22-12 AWG, 0.2-2.5 mm ²	22-12 AWG, 0.2-2.5 mm ²	22-12 AWG, 0.2-2.5 mm ²	22-12 AWG, 0.2-2.5 mm ²
Voltage Rating	300 V, 800 V	300 V, 800 V	300 V, 800 V	300 V, 800 V	300 V, 800 V	300 V, 800 V	300 V, 800 V
Current Rating	10 A, 17 A	10 A, 17 A	20 A, 24 A	20 A, 24 A	20 A, 24 A	20 A, 24 A	20 A, 24 A
Insulation Material	Polyamide 66	Polyamide 66	Polyamide 66	Polyamide 66	Polyamide 66	Polyamide 66	Polyamide 66

Installation Instructions

Wire Stripping Length	8 mm	8 mm	8 mm	8 mm
Screwdriver	0.5x3 mm	0.5x3 mm	0.5x3 mm	0.5x3 mm

Terminal Blocks

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Grey (standard)	CM1.5S	100	CM1.5S2	100	CM2.5S	100	CM2.5S2	100
Red R	CM1.5S/R	100	CM1.5S2/R	100	CM2.5S/R	100	CM2.5S2/R	100
Blue BU	CM1.5S/BU	100	CM1.5S2/BU	100	CM2.5S/BU	100	CM2.5S2/BU	100
Black BL	CM1.5S/BL	100	CM1.5S2/BL	100	CM2.5S/BL	100	CM2.5S2/BL	100
Orange O	CM1.5S/O	100	CM1.5S2/O	100	CM2.5S/O	100	CM2.5S2/O	100
Green G	CM1.5S/G	100	CM1.5S2/G	100	CM2.5S/G	100	CM2.5S2/G	100
Yellow Y	CM1.5S/Y	100	CM1.5S2/Y	100	CM2.5S/Y	100	CM2.5S2/Y	100
White W	CM1.5S/W	100	CM1.5S2/W	100	CM2.5S/W	100	CM2.5S2/W	100

Accessories

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
End Plate	EPCM1.5S	50	EPCM1.5S	50	EPCM2.5S	50	EPCM2.5S	50
Marking Tag	MT4	100	MT4	100	MT4	100	MT4	100

