ISSUE DATE: 06/26/2014 3.94 100 <del><</del> 6.72 170.69 → .56 14.30 -OPTIONAL BACK PANEL SHOWN 0.100 [2.54mm] TH'K- ALUMINUM 0.075 [1.91mm] TH'K- WHITE STEEL .88[22.23] (2) POLYCARBONATE FLANGES (GLUED) (4) EACH #10-32 BRASS-INSERTS, AND STAINLESS STEEL FLANGE AND FEET SCREWS 6.50 165.10 .10 2.54 4.06 103.02 **BACK VIEW** 7.63 193.79 -6.75 171.44 → 5.19 [131.75] <del><</del> STAINLESS STEEL 6.88 174.74 HINGE PIN SLOT MAX DIST SLOT DIST FRONT VIEW WITH COVER REMOVED AND BACK PANEL DISPLAYED 8X R.170[4.32] 4.00 101.60 CLOSED CELL NEOPRENE GASKET 4.81[122.24] -NON-METALLIC LOCKABLE SNAP LATCH LOCATED ON CENTER 4.25 107.95 4.81 122.24 .14 3.68 6.03 [153.29] -(4) EACH #10-32 BRASS INSERTS AND PLATED CARBON STEEL SCREWS WITH WASHERS <del>></del>4.25[ 107.95 ] 6.26 [159.01] PART No. PCJ664NLF for more information visit www.hammfg.com

MATERIAL: BOX- INJECTED POLYCARBONATE STANDARD COVER- INJECTED POLYCARBONATE CLEAR COVER-INJECTED POLYCARBONATE

Data subject to change without notice Drawing Not to Scale