Quality Products. Service Excellence.

Compact LED Light Kit LEDLK Series

Our compact LED light kit provides efficient lighting solution for most enclosure applications without taking up valuable interior space. Available in magnet or screw mounting and AC or DC power options.



Features

- Housing constructed in transparent plastic.
- · Screw or magnet mounting.
- · Available with rocker switch or motion sensor.
- Easily connect up to ten (10) light kits together in a daisy chain using LEDXXCORDCON cords.
- Connection: 2-pole plug with snap lock; AC: max. 2.5 A / AC 240 V, white connector; DC: max. 2.5 A / DC 60 V, blue connector.
- Requires hard-wired connection using LEDXXCORDPOWR power cord with leads and plug or power brick (not included).

Specifications

- LED provide 400 Lm at 120° (1,200 Lm at 360° or equivalent 95W light bulb).
- LED temperature 6,000 to 7,000 K.
- Operating / Storage temperature: -22 to +140 °F (-30 to +60 °C) / -40 to +185 °F (-40 to +85 °C).
- Operating / Storage humidity: max. 90 %RH (non-condensing).
- Service life: 60,000 hrs. at 68 °F (20 °C).
- Max. 5 W power consumption (~ 75 W incandescent bulb)
- Protection class / Protection type: II (double insulated) / IP20



Note that the cord on this product is intended to be hard-wired. There are currently no standard plug types for this product.

Gallery



Accessories

Power Cords

LED Light Kits

Part No.	Voltage	On/Off	Mount
LEDACSWMAG	90-260V AC	Switch	Magnet
LEDACMSMAG	90-260V AC	Sensor	Magnet
LEDACSWSCR	90-260V AC	Switch	Screw







Part No.	Voltage	On/Off	Mount
LEDACMSSCR	90-260V AC	Sensor	Screw
LEDDCSWMAG	20-60V DC	Switch	Magnet
LEDDCMSMAG	20-60V DC	Sensor	Magnet
LEDDCSWSCR	20-60V DC	Switch	Screw
LEDDCMSSCR	20-60V DC	Sensor	Screw

LED Light Kit Cords

Part No.	Туре	Source	Length
LEDACCORDPOW	Power Cord w/leads	AC	78.75
LEDDCCORDPOW	Power Cord w/leads	DC	78.75
LEDACCORDCON	Connector/Daisy Chain Cord	AC	39.38
LEDDCCORDCON	Connector/Daisy Chain Cord	DC	39.38

Light Channel Hardware

Part No.	Description	
LCMTG1032	Light channel mounting hardware - 4 x spring nuts/10-32 screws	

Data subject to change without notice

© 2022. Hammond Manufacturing Ltd. All rights reserved.

