

AT-PP adapter grommets

based on KT large, for PushPull connection technology / IP65



The grommet AT-PP is constructed on the basis of a large KT cable grommet. The polyamide body is moulded with elastomer.

The cut-out enables a screw assembly of all compact connector housings based on the PushPull device connection technology.

The insertion of AT-PP into an icotek cable entry frame enables the routing of cables with and without connectors in combination with the creation of interfaces for PushPull connectors within one cable entry system. Separate cut-outs for connectors are no longer necessary.

AT-PP provides ingress protection of up to IP65.

IP54

HL3
EN 45545-2

Made in
Germany

IP55

ECOLAB
certified

IP64

UV
ISO 4892-2A

IP65

RoHS
compliant

REACH

REACH
COMPLIANCE


Specifications

IP rating (EN 60529)	IP54, IP55, IP64, IP65
Material	Elastomer Body: Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 90 C°
Properties	silicone free, halogen free

Advantages & Benefits

- By utilising the AT-PP grommet, connectors can be integrated directly into the cable entry frame
- Separate cut-outs for connectors are no longer necessary
- Space-saving solution
- Grommet is suitable for PushPull housings
- Cost-saving assembly

Product types & Sizes

AT-PP	Part No.	39961
	EAN	4251269322570
	PU	5
	Length	42 mm
	Width	41,5 mm
	Height	19 mm
	Mounting height	2 mm