

BPK plastic blank plates

for screw assembly / IP64 / UL Type 12



IP54

REACH COMPLIANCE

IP64

Made in Germany

UL TYPE 12

CE

RoHS compliant

Specifications

IP rating (EN 60529)	IP54, IP64
UL Type (UL 50E)	UL Type 12
Material	Polypropylene Integrated sealing lip: Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-30 C° to 110 C°
Properties	silicone free, halogen free
Mounting options	Screw type mounting

Product types & Sizes

	Part No.	42024	Max. cut-out width	36 mm
	EAN	4251269307515	Cut-out size	112 x 36 mm
	PU	10	No. of screw holes	4
	Length	148 mm	Diam. of screw holes	5,5 mm
	Width	53 mm		
	Height	10,3 mm		
	Max. cut-out length	112 mm		

	Part No.	42016	Max. cut-out width	36 mm
	EAN	4251269307478	Cut-out size	86 x 36 mm
	PU	10	No. of screw holes	4
	Length	121 mm	Diam. of screw holes	5,5 mm
	Width	53 mm		
	Height	10,3 mm		
	Max. cut-out length	86 mm		

 Integrated gasket

Advantages & Benefits

BPK 10 	Part No.	42015	Max. cut-out width	36 mm
	EAN	4251269307454	Cut-out size	65 × 36 mm
	PU	10	No. of screw holes	4
	Length	101 mm	Diam. of screw holes	5,5 mm
	Width	53 mm		
	Height	10 mm		
	Max. cut-out length	65 mm		

BPK-B 	Part No.	42010	Max. cut-out width	46 mm
	EAN	4251269307393	Cut-out size	46 × 46 mm
	PU	10	No. of screw holes	4
	Length	76 mm	Diam. of screw holes	5,5 mm
	Width	53 mm		
	Height	10,3 mm		
	Max. cut-out length	46 mm		

BPK-JFX 	Part No.	42620	Diam. of screw holes	6,9 mm
	EAN	4251269309045		
	PU	5		
	Length	88 mm		
	Width	88 mm		
	Height	9 mm		
	No. of screw holes	4		

APEX

MACHINE