

KEL-BES-S split brush plate

for cable pass-through



Specifications

Material	Polyamide Brushes: Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-20 C° to 90 C°
Properties	silicone free, halogen free
Mounting options	Screw type mounting,Riveting

Product types & Sizes

KEL-BES-S 24



Part No.	51522	Cut-out size	112 x 36 mm
EAN	4251269316609	No. of screw holes	4
PU	10	Diam. of screw holes	5,8 mm
Length	147 mm		
Width	58 mm		
Height	10 mm		
Mounting height	10 mm		

KEL-BES-S 24 with expanding rivets



Part No.	51522.002	Cut-out size	112 x 36 mm
EAN	4251269320705	No. of screw holes	4
PU	10	Diam. of screw holes	5,8 mm
Length	147 mm		
Width	58 mm		
Height	10 mm		
Mounting height	10 mm		

Advantages & Benefits

- Fast and easy assembly
- Subsequent assembly possible
- Versatile utilisation
- Allows reduced airflow while filtering out dust, hair and larger particulate matter
- Visual screening
- Protects cables against wear due to sharp edges of the cut-out

KEL-BES-S 16

Part No.	51521
EAN	4251269316593
PU	10
Length	120 mm
Width	58 mm
Height	10 mm
Mounting height	10 mm

Cut-out size	86 × 36 mm
No. of screw holes	4
Diam. of screw holes	5,8 mm

**KEL-BES-S 16 with
expanding rivets**

Part No.	51521.002
EAN	4251269320699
PU	10
Length	120 mm
Width	58 mm
Height	10 mm
Mounting height	10 mm

Cut-out size	86 × 36 mm
No. of screw holes	4
Diam. of screw holes	5,8 mm

KEL-BES-S 10

Part No.	51520
EAN	4251269316586
PU	10
Length	100 mm
Width	58 mm
Height	10 mm
Mounting height	10 mm

Cut-out size	65 × 36 mm
No. of screw holes	4
Diam. of screw holes	5,8 mm

**KEL-BES-S 10 with
expanding rivets**

Part No.	51520.002
EAN	4251269320682
PU	10
Length	100 mm
Width	58 mm
Height	10 mm
Mounting height	10 mm

Cut-out size	65 × 36 mm
No. of screw holes	4
Diam. of screw holes	5,8 mm