

KEL-BES brush plate

for cable pass-through



Brush plates KEL-BES for routing cables into server racks, control panels and electrical enclosures. KEL-BES is also an ideal solution for entry and exit of cables that are routed inside raised floors, e.g. in computer centres.

The brush plates can either be mounted via screws or viaexpanding rivets.

The KEL-BES plates match exactly the cut-out dimensions 10-, 16- and 24-pin standard industrial connectors.



Specifications

Material	Polyamide Brushes: Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-20 C° to 90 C°
Properties	silicone free, halogen free
Mounting options	Screw type mounting,Riveting

Advantages & Benefits

- Fast and easy assembly
- Versatile utilisation
- Allows reduced airflow while filtering out dust, hair and larger particulate matter
- Visual screening
- Protects cables against wear due to sharp edges of the cut-out

Product types & Sizes

KEL-BES 24



Part No.	51515	Cut-out size	112 × 36 mm
EAN	4251269315442	No. of screw holes	4
PU	10	Diam. of screw holes	5,8 mm
Length	147 mm		
Width	58 mm		
Height	10 mm		
Mounting height	10 mm		

KEL-BES 16



Part No.	51510	Cut-out size	86 × 36 mm
EAN	4251269315435	No. of screw holes	4
PU	10	Diam. of screw holes	5,8 mm
Length	120 mm		
Width	58 mm		
Height	10 mm		
Mounting height	10 mm		

KEL-BES 10



Part No.
EAN
PU
Length
Width
Height
Mounting height

51505
4251269315428
10
100 mm
58 mm
10 mm
10 mm

Cut-out size
No. of screw holes
Diam. of screw holes

65 × 36 mm
4
5,8 mm

