

# KEL-DP multi-membrane cable entry plates

pluggable, with high cable density / IP64 / UL Type 12



KEL-DP entry plates are designed for routing cables without connectors, hoses or fibre optics in limited space.

The KEL-DP products are an easy to assemble and cost saving alternative to traditional cable glands. Simply make a small hole in the thin membrane and push the cables through. The KEL-DP provides protection IP64 / UL type 12.

The KEL-DP matches exactly the cut-out dimensions of 6-, 10-, 16- and 24-pin standard industrial connectors. The very compact size KEL-DP-E is designed for routing cables in very small space. Through a cut-out of only 18 x 112 mm, up to 21 cables can be easily routed and sealed. A special rib ensures a centred fit in the cut-outs.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

IP54

IP64

UL TYPE  
12

C  
UL  
US

ISO 9001  
CERTIFIED  
ENGLAND

RINA

HL3  
EN 45545-2

EN 61373

ECOLAB  
certified

ISO 4892-2A

PNEUMATICS

RoHS  
compliant

REACH  
COMPLIANCE

Made in  
Germany

## Specifications

|                       |                             |
|-----------------------|-----------------------------|
| IP rating (EN 60529)  | IP54, IP64                  |
| UL Type (UL 50E)      | UL Type 12                  |
| Material              | Elastomer                   |
| Flame class           | UL94-V0, self-extinguishing |
| Operating temperature | -30 C° to 100 C°            |
| Properties            | halogen free, silicone free |
| Mounting options      | Snap-in                     |

## Advantages & Benefits

- Quick assembly without tools
- High cable density
- Cost-effective solution
- Hygienic design - free of dirt-collecting recesses

## Product types & Sizes

KEL-DP 24|12 A gy



|                        |                         |
|------------------------|-------------------------|
| Part No.               | 43508                   |
| EAN                    | 4251269309830           |
| PU                     | 10                      |
| For max. no. of cables | 12                      |
| Color                  | grau (ähnlich RAL 7035) |
| Length                 | 142 mm                  |
| Width                  | 44 mm                   |

|                         |                |
|-------------------------|----------------|
| Height                  | 12             |
| Mounting height         | 5 mm           |
| Cut-out size            | 112 x 36 mm    |
| For min. wall thickness | 1,5 mm         |
| For max. wall thickness | 2,5 mm         |
| Clamping range          | 12 x 1 - 15 mm |

**KEL-DP 24|12 A bk**

|                        |                      |                         |                       |
|------------------------|----------------------|-------------------------|-----------------------|
| Part No.               | <b>50508</b>         | Height                  | <b>12</b>             |
| EAN                    | <b>4251269314612</b> | Mounting height         | <b>5 mm</b>           |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>    |
| For max. no. of cables | <b>12</b>            | For min. wall thickness | <b>1,5 mm</b>         |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>2,5 mm</b>         |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>12 x 1 - 15 mm</b> |
| Width                  | <b>44 mm</b>         |                         |                       |

**KEL-DP 24|14 A gy**

|                        |                                |                         |                         |
|------------------------|--------------------------------|-------------------------|-------------------------|
| Part No.               | <b>43512</b>                   | Height                  | <b>12</b>               |
| EAN                    | <b>4251269309854</b>           | Mounting height         | <b>5 mm</b>             |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>      |
| For max. no. of cables | <b>14</b>                      | For min. wall thickness | <b>1,5 mm</b>           |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>           |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>14 x 1 - 12.1 mm</b> |
| Width                  | <b>44 mm</b>                   |                         |                         |

**KEL-DP 24|14 B gy**

|                        |                                |                         |                         |
|------------------------|--------------------------------|-------------------------|-------------------------|
| Part No.               | <b>43522</b>                   | Height                  | <b>12</b>               |
| EAN                    | <b>4251269309939</b>           | Mounting height         | <b>5 mm</b>             |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>      |
| For max. no. of cables | <b>14</b>                      | For min. wall thickness | <b>2,8 mm</b>           |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>4 mm</b>             |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>14 x 1 - 12.1 mm</b> |
| Width                  | <b>44 mm</b>                   |                         |                         |

**KEL-DP 24|14 A bk**

|                        |                      |                         |                         |
|------------------------|----------------------|-------------------------|-------------------------|
| Part No.               | <b>50512</b>         | Height                  | <b>12</b>               |
| EAN                    | <b>4251269314636</b> | Mounting height         | <b>5 mm</b>             |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>      |
| For max. no. of cables | <b>14</b>            | For min. wall thickness | <b>1,5 mm</b>           |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>2,5 mm</b>           |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>14 x 1 - 12.1 mm</b> |
| Width                  | <b>44 mm</b>         |                         |                         |

**KEL-DP 24|14 B bk**

|                        |                      |                         |                         |
|------------------------|----------------------|-------------------------|-------------------------|
| Part No.               | <b>50522</b>         | Height                  | <b>12</b>               |
| EAN                    | <b>4251269314711</b> | Mounting height         | <b>5 mm</b>             |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>      |
| For max. no. of cables | <b>14</b>            | For min. wall thickness | <b>2,8 mm</b>           |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>4 mm</b>             |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>14 x 1 - 12.1 mm</b> |
| Width                  | <b>44 mm</b>         |                         |                         |

**KEL-DP 24|17 A gy**

|                        |                                |                         |                         |
|------------------------|--------------------------------|-------------------------|-------------------------|
| Part No.               | <b>43514</b>                   | Height                  | <b>12</b>               |
| EAN                    | <b>4251269309861</b>           | Mounting height         | <b>5 mm</b>             |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>      |
| For max. no. of cables | <b>17</b>                      | For min. wall thickness | <b>1,5 mm</b>           |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>           |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>5 x 1 - 10.5 mm</b>  |
| Width                  | <b>44 mm</b>                   |                         | <b>12 x 1 - 12.6 mm</b> |

**KEL-DP 24|17 B gy**

|                        |                                |                         |                         |
|------------------------|--------------------------------|-------------------------|-------------------------|
| Part No.               | <b>43523</b>                   | Height                  | <b>12</b>               |
| EAN                    | <b>4251269309946</b>           | Mounting height         | <b>5 mm</b>             |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>      |
| For max. no. of cables | <b>17</b>                      | For min. wall thickness | <b>2,8 mm</b>           |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>4 mm</b>             |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>5 x 1 - 10.5 mm</b>  |
| Width                  | <b>44 mm</b>                   |                         | <b>12 x 1 - 12.6 mm</b> |

**KEL-DP 24|17 A bk**

|                        |                      |                         |                         |
|------------------------|----------------------|-------------------------|-------------------------|
| Part No.               | <b>50514</b>         | Height                  | <b>12</b>               |
| EAN                    | <b>4251269314643</b> | Mounting height         | <b>5 mm</b>             |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>      |
| For max. no. of cables | <b>17</b>            | For min. wall thickness | <b>1,5 mm</b>           |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>2,5 mm</b>           |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>5 x 1 - 10.5 mm</b>  |
| Width                  | <b>44 mm</b>         |                         | <b>12 x 1 - 12.6 mm</b> |

**KEL-DP 24|17 B bk**

|                        |                      |                         |                         |
|------------------------|----------------------|-------------------------|-------------------------|
| Part No.               | <b>50523</b>         | Height                  | <b>12</b>               |
| EAN                    | <b>4251269314728</b> | Mounting height         | <b>5 mm</b>             |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>      |
| For max. no. of cables | <b>17</b>            | For min. wall thickness | <b>2,8 mm</b>           |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>4 mm</b>             |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>5 x 1 - 10.5 mm</b>  |
| Width                  | <b>44 mm</b>         |                         | <b>12 x 1 - 12.6 mm</b> |

**KEL-DP 24|18 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43515</b>                   | Height                  | <b>12</b>              |
| EAN                    | <b>4251269309878</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>18</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>4 x 1 - 6.5 mm</b>  |
| Width                  | <b>44 mm</b>                   |                         | <b>5 x 1 - 10.5 mm</b> |
|                        |                                |                         | <b>5 x 1 - 12.6 mm</b> |
|                        |                                |                         | <b>4 x 1 - 16.1 mm</b> |

**KEL-DP 24|18 B gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43528</b>                   | Height                  | <b>12</b>              |
| EAN                    | <b>4251269309991</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>18</b>                      | For min. wall thickness | <b>2,8 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>4 mm</b>            |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>4 x 1 - 6.5 mm</b>  |
| Width                  | <b>44 mm</b>                   |                         | <b>5 x 1 - 10.5 mm</b> |
|                        |                                |                         | <b>5 x 1 - 12.6 mm</b> |
|                        |                                |                         | <b>4 x 1 - 16.1 mm</b> |

**KEL-DP 24|18 A bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50515</b>         | Height                  | <b>12</b>              |
| EAN                    | <b>4251269314650</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>18</b>            | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>4 x 1 - 6.5 mm</b>  |
| Width                  | <b>44 mm</b>         |                         | <b>5 x 1 - 10.5 mm</b> |
|                        |                      |                         | <b>5 x 1 - 12.6 mm</b> |
|                        |                      |                         | <b>4 x 1 - 16.1 mm</b> |

**KEL-DP 24|18 B bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50528</b>         | Height                  | <b>12</b>              |
| EAN                    | <b>4251269314773</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>18</b>            | For min. wall thickness | <b>2,8 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>4 mm</b>            |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>4 x 1 - 6.5 mm</b>  |
| Width                  | <b>44 mm</b>         |                         | <b>5 x 1 - 10.5 mm</b> |
|                        |                      |                         | <b>5 x 1 - 12.6 mm</b> |
|                        |                      |                         | <b>4 x 1 - 16.1 mm</b> |

**KEL-DP 24|19 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43516</b>                   | Height                  | <b>12</b>              |
| EAN                    | <b>4251269309885</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>19</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>12 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>7 x 1 - 12.1 mm</b> |

**KEL-DP 24|19 B gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43524</b>                   | Height                  | <b>12</b>              |
| EAN                    | <b>4251269309953</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>19</b>                      | For min. wall thickness | <b>2,8 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>4 mm</b>            |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>12 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>7 x 1 - 12.1 mm</b> |

**KEL-DP 24|19 A bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50516</b>         | Height                  | <b>12</b>              |
| EAN                    | <b>4251269314667</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>19</b>            | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>12 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>         |                         | <b>7 x 1 - 12.1 mm</b> |

**KEL-DP 24|19 B bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50524</b>         | Height                  | <b>12</b>              |
| EAN                    | <b>4251269314735</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>19</b>            | For min. wall thickness | <b>2,8 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>4 mm</b>            |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>12 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>         |                         | <b>7 x 1 - 12.1 mm</b> |

**KEL-DP 24|26 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43518</b>                   | Height                  | <b>12</b>              |
| EAN                    | <b>4251269309892</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>26</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>16 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>4 x 1 - 12.1 mm</b> |

**KEL-DP 24|26 B gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43525</b>                   | Height                  | <b>12</b>              |
| EAN                    | <b>4251269309960</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>26</b>                      | For min. wall thickness | <b>2,8 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>4 mm</b>            |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>16 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>4 x 1 - 12.1 mm</b> |
|                        |                                |                         | <b>4 x 1 - 16.1 mm</b> |

**KEL-DP 24|26 A bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50518</b>         | Height                  | <b>12</b>              |
| EAN                    | <b>4251269314674</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>26</b>            | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>16 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>         |                         | <b>4 x 1 - 12.1 mm</b> |
|                        |                      |                         | <b>4 x 1 - 16.1 mm</b> |

**KEL-DP 24|26 B bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50525</b>         | Height                  | <b>12</b>              |
| EAN                    | <b>4251269314742</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>26</b>            | For min. wall thickness | <b>2,8 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>4 mm</b>            |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>16 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>         |                         | <b>4 x 1 - 12.1 mm</b> |
|                        |                      |                         | <b>4 x 1 - 16.1 mm</b> |

**KEL-DP 24|42 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43511</b>                   | Height                  | <b>12</b>              |
| EAN                    | <b>4251269309847</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>42</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>12 x 1 - 7.2 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>17 x 1 - 6.4 mm</b> |
|                        |                                |                         | <b>12 x 1 - 5 mm</b>   |
|                        |                                |                         | <b>1 x 1 - 4.7 mm</b>  |

**KEL-DP 24|42 B gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43521</b>                   | Height                  | <b>12</b>              |
| EAN                    | <b>4251269309922</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>42</b>                      | For min. wall thickness | <b>2,8 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>4 mm</b>            |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>12 x 1 - 7.2 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>17 x 1 - 6.4 mm</b> |
|                        |                                |                         | <b>12 x 1 - 5 mm</b>   |
|                        |                                |                         | <b>1 x 1 - 4.7 mm</b>  |

**KEL-DP 24/42 A bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50511</b>         | Height                  | <b>12</b>              |
| EAN                    | <b>4251269314629</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>42</b>            | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>12 x 1 - 7.2 mm</b> |
| Width                  | <b>44 mm</b>         |                         | <b>17 x 1 - 6.4 mm</b> |
|                        |                      |                         | <b>12 x 1 - 5 mm</b>   |
|                        |                      |                         | <b>1 x 1 - 4.7 mm</b>  |

**KEL-DP 24/42 B bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50521</b>         | Height                  | <b>12</b>              |
| EAN                    | <b>4251269314704</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>42</b>            | For min. wall thickness | <b>2,8 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>4 mm</b>            |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>12 x 1 - 7.2 mm</b> |
| Width                  | <b>44 mm</b>         |                         | <b>17 x 1 - 6.4 mm</b> |
|                        |                      |                         | <b>12 x 1 - 5 mm</b>   |
|                        |                      |                         | <b>1 x 1 - 4.7 mm</b>  |

**KEL-DP 24/48 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43519</b>                   | Height                  | <b>12</b>              |
| EAN                    | <b>4251269309908</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>48</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>48 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>                   |                         |                        |

**KEL-DP 24/48 B gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43526</b>                   | Height                  | <b>12</b>              |
| EAN                    | <b>4251269309977</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>48</b>                      | For min. wall thickness | <b>2,8 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>4 mm</b>            |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>48 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>                   |                         |                        |

**KEL-DP 24/48 A bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50519</b>         | Height                  | <b>12</b>              |
| EAN                    | <b>4251269314681</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>48</b>            | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>48 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>         |                         |                        |

**KEL-DP 24/48 B bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50526</b>         | Height                  | <b>12</b>              |
| EAN                    | <b>4251269314759</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>48</b>            | For min. wall thickness | <b>2,8 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>4 mm</b>            |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>48 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>         |                         |                        |

**KEL-DP 24|50 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43520</b>                   | Height                  | <b>12</b>              |
| EAN                    | <b>4251269309915</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>50</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>33 x 1 - 5.3 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>9 x 1 - 6.4 mm</b>  |
|                        |                                |                         | <b>8 x 1 - 8.3 mm</b>  |

**KEL-DP 24|50 B gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43527</b>                   | Height                  | <b>12</b>              |
| EAN                    | <b>4251269309984</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>50</b>                      | For min. wall thickness | <b>2,8 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>4 mm</b>            |
| Length                 | <b>142 mm</b>                  | Clamping range          | <b>33 x 1 - 5.3 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>9 x 1 - 6.4 mm</b>  |
|                        |                                |                         | <b>8 x 1 - 8.3 mm</b>  |

**KEL-DP 24|50 A bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50520</b>         | Height                  | <b>12</b>              |
| EAN                    | <b>4251269314698</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>50</b>            | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>33 x 1 - 5.3 mm</b> |
| Width                  | <b>44 mm</b>         |                         | <b>9 x 1 - 6.4 mm</b>  |
|                        |                      |                         | <b>8 x 1 - 8.3 mm</b>  |

**KEL-DP 24|50 B bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50527</b>         | Height                  | <b>12</b>              |
| EAN                    | <b>4251269314766</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | Cut-out size            | <b>112 x 36 mm</b>     |
| For max. no. of cables | <b>50</b>            | For min. wall thickness | <b>2,8 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>4 mm</b>            |
| Length                 | <b>142 mm</b>        | Clamping range          | <b>33 x 1 - 5.3 mm</b> |
| Width                  | <b>44 mm</b>         |                         | <b>9 x 1 - 6.4 mm</b>  |
|                        |                      |                         | <b>8 x 1 - 8.3 mm</b>  |

**KEL-DP 16|10 A gy**

|                        |                                |                         |                         |
|------------------------|--------------------------------|-------------------------|-------------------------|
| Part No.               | <b>43460</b>                   | Height                  | <b>12 mm</b>            |
| EAN                    | <b>4251269320750</b>           | Mounting height         | <b>5 mm</b>             |
| PU                     | <b>10</b>                      | Cut-out size            | <b>86 x 36 mm</b>       |
| For max. no. of cables | <b>10</b>                      | For min. wall thickness | <b>1,5 mm</b>           |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>           |
| Length                 | <b>96 mm</b>                   | Clamping range          | <b>10 x 1 - 12.2 mm</b> |
| Width                  | <b>44 mm</b>                   |                         |                         |

**KEL-DP 16|11 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43461</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269320767</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>86 x 36 mm</b>      |
| For max. no. of cables | <b>11</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>96 mm</b>                   | Clamping range          | <b>3 x 1 - 10.5 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>8 x 1 - 12.6 mm</b> |

**KEL-DP 16|20 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43462</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269320774</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>86 × 36 mm</b>      |
| For max. no. of cables | <b>20</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>96 mm</b>                   | Clamping range          | <b>20 x 1 - 8.3 mm</b> |
| Width                  | <b>44 mm</b>                   |                         |                        |

**KEL-DP 16|22 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43463</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269320781</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>86 × 36 mm</b>      |
| For max. no. of cables | <b>22</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>96 mm</b>                   | Clamping range          | <b>5 x 1 - 12.1 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>4 x 1 - 8.3 mm</b>  |
|                        |                                |                         | <b>13 x 1 - 6.5 mm</b> |

**KEL-DP 16|23 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43464</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269320798</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>86 × 36 mm</b>      |
| For max. no. of cables | <b>23</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>96 mm</b>                   | Clamping range          | <b>18 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>5 x 1 - 12.1 mm</b> |

**KEL-DP 16|26 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43465</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269320804</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>86 × 36 mm</b>      |
| For max. no. of cables | <b>26</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>96 mm</b>                   | Clamping range          | <b>19 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>7 x 1 - 8.3 mm</b>  |


**KEL-DP 10|8 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43466</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269324000</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>65 × 36 mm</b>      |
| For max. no. of cables | <b>8</b>                       | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>75 mm</b>                   | Clamping range          | <b>8 x 1 - 12.6 mm</b> |
| Width                  | <b>44 mm</b>                   |                         |                        |

**KEL-DP 10|12 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43467</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269324017</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>65 × 36 mm</b>      |
| For max. no. of cables | <b>12</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>75 mm</b>                   | Clamping range          | <b>4 x 1 - 6.5 mm</b>  |
| Width                  | <b>44 mm</b>                   |                         | <b>4 x 1 - 8.3 mm</b>  |
|                        |                                |                         | <b>4 x 1 - 12.6 mm</b> |




**KEL-DP 10|14 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43468</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269324024</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>65 × 36 mm</b>      |
| For max. no. of cables | <b>14</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>75 mm</b>                   | Clamping range          | <b>14 x 1 - 8.3 mm</b> |
| Width                  | <b>44 mm</b>                   |                         |                        |

**KEL-DP 10|16 A gy**

|                        |                                |                         |                         |
|------------------------|--------------------------------|-------------------------|-------------------------|
| Part No.               | <b>43469</b>                   | Height                  | <b>12 mm</b>            |
| EAN                    | <b>4251269324031</b>           | Mounting height         | <b>5 mm</b>             |
| PU                     | <b>10</b>                      | Cut-out size            | <b>65 × 36 mm</b>       |
| For max. no. of cables | <b>16</b>                      | For min. wall thickness | <b>1,5 mm</b>           |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>           |
| Length                 | <b>75 mm</b>                   | Clamping range          | <b>4 x 1 - 6.5 mm</b>   |
| Width                  | <b>44 mm</b>                   |                         | <b>12 x 1 - 12.6 mm</b> |

**KEL-DP 10|26 A gy**


|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43470</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269324048</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>65 × 36 mm</b>      |
| For max. no. of cables | <b>26</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>75 mm</b>                   | Clamping range          | <b>26 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>                   |                         |                        |

**KEL-DP 6|6 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43450</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269320712</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>52 × 36 mm</b>      |
| For max. no. of cables | <b>6</b>                       | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>62 mm</b>                   | Clamping range          | <b>6 x 1 - 12.1 mm</b> |
| Width                  | <b>44 mm</b>                   |                         |                        |

**KEL-DP 6|12 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43451</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269320729</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>52 × 36 mm</b>      |
| For max. no. of cables | <b>12</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>62 mm</b>                   | Clamping range          | <b>8 x 1 - 6.5 mm</b>  |
| Width                  | <b>44 mm</b>                   |                         | <b>2 x 1 - 12.6 mm</b> |
|                        |                                |                         | <b>2 x 1 - 16.1 mm</b> |

**KEL-DP 6|14 A gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43452</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269320736</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | Cut-out size            | <b>52 × 36 mm</b>      |
| For max. no. of cables | <b>14</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>62 mm</b>                   | Clamping range          | <b>10 x 1 - 6.5 mm</b> |
| Width                  | <b>44 mm</b>                   |                         | <b>4 x 1 - 10.5 mm</b> |

**KEL-DP 6|25 A gy**

|                        |                                |                         |                       |
|------------------------|--------------------------------|-------------------------|-----------------------|
| Part No.               | <b>43453</b>                   | Height                  | <b>12 mm</b>          |
| EAN                    | <b>4251269320743</b>           | Mounting height         | <b>5 mm</b>           |
| PU                     | <b>10</b>                      | Cut-out size            | <b>52 x 36 mm</b>     |
| For max. no. of cables | <b>25</b>                      | For min. wall thickness | <b>1,5 mm</b>         |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | For max. wall thickness | <b>2,5 mm</b>         |
| Length                 | <b>62 mm</b>                   | Clamping range          | <b>21 x 1 - 5 mm</b>  |
| Width                  | <b>44 mm</b>                   |                         | <b>4 x 1 - 8.3 mm</b> |

**KEL-DP-E 46|7 gy**

|                        |                                |                         |                       |
|------------------------|--------------------------------|-------------------------|-----------------------|
| Part No.               | <b>43585</b>                   | Height                  | <b>12 mm</b>          |
| EAN                    | <b>4251269310287</b>           | Mounting height         | <b>5 mm</b>           |
| PU                     | <b>10</b>                      | For min. wall thickness | <b>1,5 mm</b>         |
| For max. no. of cables | <b>7</b>                       | For max. wall thickness | <b>2,5 mm</b>         |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | Clamping range          | <b>5 x 1 - 8.3 mm</b> |
| Length                 | <b>62 mm</b>                   |                         | <b>2 x 1 - 6.5 mm</b> |
| Width                  | <b>25 mm</b>                   |                         |                       |

**KEL-DP-E 46|7 bk**

|                        |                      |                         |                       |
|------------------------|----------------------|-------------------------|-----------------------|
| Part No.               | <b>50585</b>         | Height                  | <b>12 mm</b>          |
| EAN                    | <b>4251269315008</b> | Mounting height         | <b>5 mm</b>           |
| PU                     | <b>10</b>            | For min. wall thickness | <b>1,5 mm</b>         |
| For max. no. of cables | <b>7</b>             | For max. wall thickness | <b>2,5 mm</b>         |
| Color                  | <b>schwarz</b>       | Clamping range          | <b>5 x 1 - 8.3 mm</b> |
| Length                 | <b>62 mm</b>         |                         | <b>2 x 1 - 6.5 mm</b> |
| Width                  | <b>25 mm</b>         |                         |                       |

**KEL-DP-E 46|9 gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43587</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269310294</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| For max. no. of cables | <b>9</b>                       | For max. wall thickness | <b>2,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | Clamping range          | <b>8 x 1 - 6.5 mm</b>  |
| Length                 | <b>62 mm</b>                   |                         | <b>1 x 1 - 12.1 mm</b> |
| Width                  | <b>25 mm</b>                   |                         |                        |

**KEL-DP-E 46|9 bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50587</b>         | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269315015</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | For min. wall thickness | <b>1,5 mm</b>          |
| For max. no. of cables | <b>9</b>             | For max. wall thickness | <b>2,5 mm</b>          |
| Color                  | <b>schwarz</b>       | Clamping range          | <b>8 x 1 - 6.5 mm</b>  |
| Length                 | <b>62 mm</b>         |                         | <b>1 x 1 - 12.1 mm</b> |
| Width                  | <b>25 mm</b>         |                         |                        |

**KEL-DP-E 86|13 gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43581</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269310263</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| For max. no. of cables | <b>13</b>                      | For max. wall thickness | <b>2,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | Clamping range          | <b>11 x 1 - 8.3 mm</b> |
| Length                 | <b>102 mm</b>                  |                         | <b>2 x 1 - 6.5 mm</b>  |
| Width                  | <b>25 mm</b>                   |                         |                        |

**KEL-DP-E 86|13 bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50581</b>         | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269314988</b> | External diameter       | <b>mm</b>              |
| PU                     | <b>10</b>            | Mounting height         | <b>5 mm</b>            |
| For max. no. of cables | <b>13</b>            | For min. wall thickness | <b>1,5 mm</b>          |
| Color                  | <b>schwarz</b>       | For max. wall thickness | <b>2,5 mm</b>          |
| Length                 | <b>102 mm</b>        | Clamping range          | <b>11 x 1 - 8.3 mm</b> |
| Width                  | <b>25 mm</b>         |                         | <b>2 x 1 - 6.5 mm</b>  |

**KEL-DP-E 86|17 gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43583</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269310270</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| For max. no. of cables | <b>17</b>                      | For max. wall thickness | <b>2,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | Clamping range          | <b>16 x 1 - 6.5 mm</b> |
| Length                 | <b>102 mm</b>                  |                         | <b>1 x 1 - 12.1 mm</b> |
| Width                  | <b>25 mm</b>                   |                         |                        |

**KEL-DP-E 86|17 bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50583</b>         | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269314995</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | For min. wall thickness | <b>1,5 mm</b>          |
| For max. no. of cables | <b>17</b>            | For max. wall thickness | <b>2,5 mm</b>          |
| Color                  | <b>schwarz</b>       | Clamping range          | <b>16 x 1 - 6.5 mm</b> |
| Length                 | <b>102 mm</b>        |                         | <b>1 x 1 - 12.1 mm</b> |
| Width                  | <b>25 mm</b>         |                         |                        |

**KEL-DP-E 112|16 gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43576</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269310249</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| For max. no. of cables | <b>16</b>                      | For max. wall thickness | <b>2,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | Clamping range          | <b>4 x 1 - 6.5 mm</b>  |
| Length                 | <b>128 mm</b>                  |                         | <b>11 x 1 - 8.3 mm</b> |
| Width                  | <b>25 mm</b>                   |                         | <b>1 x 1 - 12.1 mm</b> |

**KEL-DP-E 112|16 bk**

|                        |                      |                         |                        |
|------------------------|----------------------|-------------------------|------------------------|
| Part No.               | <b>50576</b>         | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269314964</b> | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>            | For min. wall thickness | <b>1,5 mm</b>          |
| For max. no. of cables | <b>16</b>            | For max. wall thickness | <b>2,5 mm</b>          |
| Color                  | <b>schwarz</b>       | Clamping range          | <b>4 x 1 - 6.5 mm</b>  |
| Length                 | <b>128 mm</b>        |                         | <b>11 x 1 - 8.3 mm</b> |
| Width                  | <b>25 mm</b>         |                         | <b>1 x 1 - 12.1 mm</b> |

**KEL-DP-E 112|21 gy**

|                        |                                |                         |                        |
|------------------------|--------------------------------|-------------------------|------------------------|
| Part No.               | <b>43578</b>                   | Height                  | <b>12 mm</b>           |
| EAN                    | <b>4251269310256</b>           | Mounting height         | <b>5 mm</b>            |
| PU                     | <b>10</b>                      | For min. wall thickness | <b>1,5 mm</b>          |
| For max. no. of cables | <b>21</b>                      | For max. wall thickness | <b>2,5 mm</b>          |
| Color                  | <b>grau (ähnlich RAL 7035)</b> | Clamping range          | <b>16 x 1 - 6.5 mm</b> |
| Length                 | <b>128 mm</b>                  |                         | <b>4 x 1 - 8.3 mm</b>  |
| Width                  | <b>25 mm</b>                   |                         | <b>1 x 1 - 12.1 mm</b> |

KEL-DP-E 112|21 bk



|                        |               |                         |                 |
|------------------------|---------------|-------------------------|-----------------|
| Part No.               | 50578         | Height                  | 12 mm           |
| EAN                    | 4251269314971 | Mounting height         | 5 mm            |
| PU                     | 10            | For min. wall thickness | 1,5 mm          |
| For max. no. of cables | 21            | For max. wall thickness | 2,5 mm          |
| Color                  | schwarz       | Clamping range          | 16 x 1 - 6.5 mm |
| Length                 | 128 mm        |                         | 4 x 1 - 8.3 mm  |
| Width                  | 25 mm         |                         | 1 x 1 - 12.1 mm |

KEL-DP-S 69|8 gy



|                        |                         |                         |                |
|------------------------|-------------------------|-------------------------|----------------|
| Part No.               | 43591                   | Height                  | 12 mm          |
| EAN                    | 4251269310300           | Mounting height         | 5 mm           |
| PU                     | 10                      | For min. wall thickness | 1,5 mm         |
| For max. no. of cables | 8                       | For max. wall thickness | 2,5 mm         |
| Color                  | grau (ähnlich RAL 7035) | Clamping range          | 8 x 1 - 7.5 mm |
| Length                 | 78 mm                   |                         |                |
| Width                  | 19,5 mm                 |                         |                |

KEL-DP-S 69|8 bk



|                        |               |                         |                |
|------------------------|---------------|-------------------------|----------------|
| Part No.               | 50591         | Height                  | 12 mm          |
| EAN                    | 4251269315022 | Mounting height         | 5 mm           |
| PU                     | 10            | For min. wall thickness | 1,5 mm         |
| For max. no. of cables | 8             | For max. wall thickness | 2,5 mm         |
| Color                  | schwarz       | Clamping range          | 8 x 1 - 7.5 mm |
| Length                 | 78 mm         |                         |                |
| Width                  | 19,5 mm       |                         |                |

APEX

MACHINE