

KT-DPF multi-range cable grommets, black

in pyramid shape, for cable diameters 3-26 mm / IP54



The KT-DPF grommets accept a wide range of cable diameters. A great benefit when the exact cable diameter is not known in advance. Due to the flexibility and unique pyramid shape, routing and flexible positioning of rigid cables is much easier compared to using conventional cable glands.

The KT-DPF grommets are not split and therefore only usable for cables without connectors.

Cutting of KT-DPF grommets: Cable diameter less 20%. It is recommended that additional strain relief be provided for the cables using a cable tie.

IP54

RIS

ECOLAB
certified

PNEUMATICS

RoHS
compliant

REACH
COMPLIANCE

Made in
Germany

Specifications


IP rating (EN 60529)	IP54
Material	Elastomer
Flame class	UL94-HB
Operating temperature	-30 C° to 90 C°
Properties	Higher chemical higher chemical resistance

Advantages & Benefits

- Large clamping range of 3 to 26 mm with only 3 grommets
- Ideal for wiring non pre-terminated cables locally
- Easy storage

Product types & Sizes

KT-DPF-A bk



Part No.	41360	Height	50 mm
EAN	4251269307102	Mounting height	33 mm
PU	10	Clamping range	1 x 3 - 12 mm
For max. no. of cables	1		
Color	schwarz		
Length	21 mm		
Width	21 mm		

KT-DPF-B bk



Part No.	41361	Height	59 mm
EAN	4251269307119	Mounting height	42 mm
PU	10	For cable type	Rundleitung
For max. no. of cables	1	Clamping range	1 x 4 - 18 mm
Color	schwarz		
Length	41,5 mm		
Width	42 mm		

KT-DPF-C bk



Part No.

EAN

PU

For max. no. of cables

Color

Length

Width

41362

4251269307126

10

1

schwarz

41,5 mm

42 mm

Height

Mounting height

For cable type

Clamping range

59 mm

42 mm

Rundleitung

1 x 14 - 26 mm

