

# KT-SC multi-range grommets

for cable diameters 5 - 28 mm / IP54



The KT-SC grommets accept a wide range of cable diameters. This is a great benefit when the exact cable diameter is not known in advance.

The single circular membrane can be peeled away to accommodate the specific diameter of the cable or hose. For this purpose, only a small hole between the rings needs to be pierced. Then the corresponding ring can be removed. The peeled-off area is always round, ensuring a secure seal around cable/hose.

The KT-SC cable grommet is based on the large KT grommet and enables flexible routing and sealing (IP54) of electrical cables and pneumatic hoses with diameters from 5 - 28 mm.

The KT-SC cable grommets are not split and therefore only usable for cables without connectors.

IP54



ECOLAB  
certified



RoHS  
compliant



Made in  
Germany

## Specifications

IP rating (EN 60529)	IP54
Material	Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free

## Advantages & Benefits

- Large clamping range of 5 to 28 mm with only one grommet
- Easy storage
- Circular membranes can be peeled off easily
- It is possible to install rigid cables at angles
- Ideal for wiring non pre-terminated cables locally

## Product types & Sizes

	KT-SC	Part No.	41485	Height	19 mm
		EAN	4251269321474	Mounting height	2 mm
		PU	10	For cable type	Rundleitung
		For max. no. of cables	1	Clamping range	1 x 5 - 28 mm
		Color	grau (ähnlich RAL 7035)		
		Length	41,5 mm		
		Width	42 mm		