## **Punch driver sets**

Hydraulic punch driver & accessories




#### Hand hydraulic punch driver

The compact, lightweight hand hydraulic punch driver makes it easy to punch holes into stainless V2A steel, mild steel, aluminium or plastics with a max. sheet thickness of 3 mm (V2A: 2 mm), due to its high hydraulic force. The cylinder of the punch driver rotates 360° on 3 axles, so maximum flexibility even in hard-to-reach places is provided.

The punch driver can be used with all icotek punches and also with punches of other manufacturers.

#### Scope of delivery:

- 1 hand hydraulic punch driver (weight: 2 kg)
- 1 draw stud Ø 9.5 mm (3/8" UNF) to Ø 19 mm (3/4" UNF), L: 105 mm
- 1 draw stud Ø 19 mm (3/4" UNF), L: 130 mm
- 1 spacer
- 1 tube lubricant
- 1 HSS co-pilot drill (multi step drill)
- 1 robust plastic storage case
- Set PRO 16-31: 1 each knockout punch M16 | M20 | M25 | M32
- Set PRO 16-63: 1 each knockout punch M16 | M20 | M25 | M32 | M40 | M50 | M63



Universally applicable single-stage foot pump with a fixed operating pressure of 450 bar and built-in pressure relief valve. Suitable for all icotek round punches, rectangular and square punches. Keeps your hands free to position the sheet metal punch precisely, especially when using larger sheet metal punches.

#### Scope of delivery:

- 1 foot pump
- 2,5 m high pressure hose including quick coupling
- 1 hydraulic cylinder for holding round and rectangular punch
- 1 draw stud for rectangular punch, Order No. 80209
- 1 draw stud for round punch (steel) M16 M25,
- Order No. 80200
- 1 multi-step drill, Order No. 80204
- 1 spacer, Order No. 80202
- 1 tube lubricant, Order No. 80203

Note: storage case not included in delivery.

## **Specifications**

Material

Aluminum

## **Advantages & Benefits**

Maximum flexibility due to 360° head rotation

Compact, lightweight aluminum design (2 kg) for fast and easy operation

High hydraulic force (60 kN, 600 bar) for easy punching

Robust plastic storage case

Punch driver also suitable for punches by other manufacturers

## **Product types & Sizes**

#### Hydraulic foot pump



Part No. EAN

4251269323690

80002

ΡU

60 kN Punching force Operating pressure 450 bar

### Punch driver set BASIC



Part No. 80000

EAN 4251269316135

PU 60 kN Punching force

Operating pressure 600 bar

## Punch driver set PRO 16-32



80005 Part No.

EAN 4251269316142

PU Punching force 60 kN Operating pressure 600 bar

# Punch driver set PRO 16-63



Part No. EAN

ΡU

Punching force Operating pressure 80006

OMAT/OL 4251269316159

60 kN



