

CDD 144 poles + 10A - 250V

enclosures:
size "77.62"

page:

C-TYPE IP65/IP66

424 - 429


W-TYPE for aggressive environments

525

E-Xtreme® corrosion proof

546

inserts, crimp connections

10A crimp contacts
silver and gold plated

PCBs interface, see article CIF 2.4 on page 670

description	part No.	part No.	part No.	part No.
without contacts (to be ordered separately)				
female inserts, No. (1-72) and (73-144)	CDDF 72	CDDF 72 N		
male inserts, No. (1-72) and (73-144)	CDDM 72	CDDM 72 N		
10A female contacts				
0,14-0,37 mm ² AWG 26-22 identification No. 1			CDFA 0.3	CDFD 0.3
0,5 mm ² AWG 20 identification No. 2			CDFA 0.5	CDFD 0.5
0,75 mm ² AWG 18 identification No. ②			CDFA 0.7	CDFD 0.7
1 mm ² AWG 18 identification No. 3			CDFA 1.0	CDFD 1.0
1,5 mm ² AWG 16 identification No. 4			CDFA 1.5	CDFD 1.5
2,5 mm ² AWG 14 identification No. 5			CDFA 2.5	CDFD 2.5
10A male contacts				
0,14-0,37 mm ² AWG 26-22 identification No. 1			CDMA 0.3	CDMD 0.3
0,5 mm ² AWG 20 identification No. 2			CDMA 0.5	CDMD 0.5
0,75 mm ² AWG 18 identification No. ②			CDMA 0.7	CDMD 0.7
1 mm ² AWG 18 identification No. 3			CDMA 1.0	CDMD 1.0
1,5 mm ² AWG 16 identification No. 4			CDMA 1.5	CDMD 1.5
2,5 mm ² AWG 14 identification No. 5			CDMA 2.5	CDMD 2.5

- characteristics according to EN 61984:

10A 250V 4kV 2

- cULus (UL for USA and Canada), certified

- rated voltage according to UL/CSA: 600V

- insulation resistance: $\geq 10 \text{ G}\Omega$

- ambient temperature limit: -40 °C ... +125 °C


- made of self-extinguishing thermoplastic resin UL 94V-0

- mechanical life: ≥ 500 cycles- contact resistance: $\leq 3 \text{ m}\Omega$


- for applications requiring higher voltages, please see the special voltage application section on page 75

- **it is recommended to crimp the contacts with crimping tools homologated by ILME** (please see the crimping tool section 10A contacts, CDF and CDM series on pages 708 - 741)

- for max. current load see the connector inserts derating diagram below; for more information see page 28




contacts side (front view)



CDF and CDM contacts

conductor section mm ²	conductor slot $\varnothing A$ (mm)	conductors stripping length B (mm)
0,14-0,37	0,9	8
0,5	1,1	8
0,75	1,3	8
1,0	1,45	8
1,5	1,8	8
2,5	2,2	6

CDD 144 poles connector inserts
Maximum current load derating diagramCR CP coding pin
with loss of one contact
(page 689)

+ for basic or high thickness gold plating, please refer to page 674