



# 7/8" MIN Series Size I Cordsets

5 & 6 Conductor MIN Series Size I Cordsets, 16AWG







Right Angle Male Cordsets | 600 Volt, 8 amps | IP69 Rating

A

MIN Series Size I Cordsets



| Connector Body Style                                                                | Part Number                                             | Cables                                                                                                   | Features                             | Color Code                                                                                                              | Faceview                                                                                            |                                                                                         |
|-------------------------------------------------------------------------------------|---------------------------------------------------------|----------------------------------------------------------------------------------------------------------|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
|    | MIN-5MP-*-R<br>(YELLOW)<br><br>MIN-5MP-*-R-B<br>(BLACK) | PVC<br>STOOW<br><b>5 X 16 AWG</b><br>600V, 8A<br>-40°C to +105°C<br>13.1mm OD                            | Industry Standard PVC                |                                                                                                                         | <br>7/8"-16UN2   |                                                                                         |
|                                                                                     | MINM-5MP-*-R                                            | Yellow PVC<br>STOOW<br>With Foil Shield<br><b>5 X 16 AWG</b><br>600V, 8A<br>-40°C to +105°C<br>13.1mm OD | Industry Standard PVC<br>Foil Shield |                                                                                                                         |                                                                                                     | <b>North American</b><br>1. White<br>2. Red<br>3. Green/Yellow<br>4. Orange<br>5. Black |
|                                                                                     | MINW-5MP-*-R                                            | Yellow TPE<br>SEOOW<br><b>5 X 16 AWG</b><br>600V, 8A<br>-40°C to +80°C<br>13.1mm OD                      | Weld Slag<br>Resistant TPE           | <b>North American<br/>Auto Color Code</b><br>1. Red/White<br>2. Red<br>3. Green/Yellow<br>4. Red/Yellow<br>5. Red/Black |                                                                                                     |                                                                                         |
|                                                                                     | MIN-5MP-*-A-R                                           | Yellow PVC<br>STOOW<br><b>5 X 16 AWG</b><br>600V, 8A<br>-40°C to +105°C<br>13.1mm OD                     | Industry Standard PVC                |                                                                                                                         |                                                                                                     |                                                                                         |
|  | MIN-6MP-*-R<br>(YELLOW)<br><br>MIN-6MP-*-R-B<br>(BLACK) | PVC<br>STOOW<br><b>6 X 16 AWG</b><br>600V, 8A<br>-40°C to +105°C<br>13.3mm OD                            | Industry Standard PVC                | <b>North American</b><br>1. White<br>2. Red<br>3. Green/Yellow<br>4. Orange<br>5. Black<br>6. Blue                      | <br>7/8"-16UN2 |                                                                                         |

\* Lengths in feet. Standard cable lengths are 3, 6, 12, 20, 30 & 50 feet. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "-SS" suffix. (e.g. MIN-6MP-3 becomes MIN-6MP-3-R-SS)

For male threaded coupling replace "MP" with "MPM". (e.g. MIN-5MP-3-R becomes MIN-5MPM-3-R)

See Page A-33 for Armored Cordset options.