



7/8" MIN Series Size I Receptacles

2, 3, 4, 5 & 6 Conductor MIN Series Size I Receptacles, 16/18/22AWG






Front Mount Receptacles | M16 x 1.5 Threads | IP69 Rating

A

MIN Series Size I Receptacles



# of Poles	Male Faceview	Color Code	Rating	Wire AWG	Male Receptacles	Female Receptacles	
						Male Threads	Female Threads
2		North American 1. White 2. Black	300V 10A	18 AWG	MIN-2MR-1-18-M16	MIN-2FR-1-18-M16	MIN-2FRF-1-18-M16
			300V 4A	22 AWG	MIN-2MR-1-22-M16	MIN-2FR-1-22-M16	MIN-2FRF-1-22-M16
3		North American 1. Green/Yellow 2. Black 3. White	300V 10A	18 AWG	MIN-3MR-1-18-M16	MIN-3FR-1-18-M16	MIN-3FRF-1-18-M16
			300V 4A	22 AWG	MIN-3MR-1-22-M16	MIN-3FR-1-22-M16	MIN-3FRF-1-22-M16
4		North American 1. Black 2. White 3. Red 4. Green/Yellow	300V 5.5A	18 AWG	MIN-4MR-1-18-M16	MIN-4FR-1-18-M16	MIN-4FRF-1-18-M16
			300V 4A	22 AWG	MIN-4MR-1-22-M16	MIN-4FR-1-22-M16	MIN-4FRF-1-22-M16
5		North American 1. White 2. Red 3. Green/Yellow 4. Orange 5. Black	300V 5.5A	18 AWG	MIN-5MR-1-18-M16	MIN-5FR-1-18-M16	MIN-5FRF-1-18-M16
			300V 4A	22 AWG	MIN-5MR-1-22-M16	MIN-5FR-1-22-M16	MIN-5FRF-1-22-M16
6		North American 1. White 2. Red 3. Green/Yellow 4. Orange 5. Black 6. Blue	300V 5.5A	18 AWG	MIN-6MR-1-18-M16	MIN-6FR-1-18-M16	MIN-6FRF-1-18-M16
			300V 4A	22 AWG	MIN-6MR-1-22-M16	MIN-6FR-1-22-M16	MIN-6FRF-1-22-M16


12" leads are standard. Longer lead lengths are available, please consult the factory for part numbers.

Standard shell is anodized aluminum, for stainless steel shell add a "SS" suffix. (e.g. MIN-3MR-1-18-M16 becomes MIN-3MR-1-18-M16-SS)

Specifications:

Shell:	Clear Anodized Aluminum
Insulator:	105°C, Oil Resistant Yellow PVC
Wire:	18 & 22 AWG: UL Style 1007/1569, 300V
Contacts:	Copper Alloy with Gold Plating
O-Ring:	NBR
Jam Nut:	Nickel Plated Brass
Temperature:	-40°C to 105°C (-40°F to +221°F)

Male & Female Receptacle (Male Threads)



Female Receptacle (Female Threads)

