



7/8" MIN Series Size I Receptacles

2, 3, 4, 5 & 6 Conductor MIN Series Size I Receptacles



Male-Female Through Panel Mount Receptacles | IP69 Rating



A

MIN Series Size I Receptacles

# of Poles	Male Faceview	Rating	Part Number	Wiring	Female Faceview
2	 7/8"-16UN2	600V 13A	MIN-2MFRF-TM	1 to 1 2 to 2	 7/8"-16UN2
3	 7/8"-16UN2	600V 13A	MIN-3MFRF-TM	1 to 1 2 to 2 3 to 3	 7/8"-16UN2
4	 7/8"-16UN2	600V 10A	MIN-4MFRF-TM	1 to 1 2 to 2 3 to 3 4 to 4	 7/8"-16UN2
5	 7/8"-16UN2	600V 8A	MIN-5MFRF-TM	1 to 1 2 to 2 3 to 3 4 to 4 5 to 5	 7/8"-16UN2
6	 7/8"-16UN2	600V 8A	MIN-6MFRF-TM	1 to 1 2 to 2 3 to 3 4 to 4 5 to 5 6 to 6	 7/8"-16UN2

Specifications:

Shell:	Nickel Plated Brass
Insulator:	105°C, Oil Resistant Yellow PVC
Contacts:	Copper Alloy with Gold Plating
Jam Nut:	Nickel Plated Brass
Thrust Washer:	Zinc Die-Cast
Sealing Washer:	NBR
Temperature:	-40°C to 105°C (-40°F to +221°F)

