

# 1 3/8" MIN Power Series Cordsets




## 3 Conductor MIN Power Series Cordsets, 10, 12 & 14AWG



Straight Male Cordsets | 600 Volt | IP67 Rating



### D PMIN Cordsets

| Connector Body Style                                                                | Part Number        | Cables                                                                             | Features                                 | Color Code                                                       | Faceview                                                                              |
|-------------------------------------------------------------------------------------|--------------------|------------------------------------------------------------------------------------|------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|    | PMIN-30MP-**       | Gray PVC<br>STOOW<br><b>3 X 10 AWG</b><br>600V, 35A<br>-40°C to +90°C<br>16.6mm OD | Industry Standard PVC                    | <b>North American</b><br>1. Green/Yellow<br>2. Black<br>3. White |    |
|                                                                                     | PMIN-34MP-**       | Gray PVC<br>STOOW<br><b>3 X 14 AWG</b><br>600V, 24A<br>-40°C to +90°C<br>13.6mm OD |                                          |                                                                  |                                                                                       |
|  | PMINW-30MP-**-C011 | Black TPE<br>AWM<br><b>3 X 10AWG</b><br>600V, 35A<br>-40°C to +90°C<br>11.9mm OD   | TC-ER, FT4<br>Weld Slag<br>Resistant TPE | <b>North American</b><br>1. Green/Yellow<br>2. Black<br>3. White |  |
|                                                                                     | PMINW-32MP-**-C011 | Black TPE<br>AWM<br><b>3 X 12AWG</b><br>600V, 28A<br>-40°C to +90°C<br>10.2mm OD   |                                          |                                                                  |                                                                                       |
|                                                                                     | PMINW-34MP-**-C011 | Black TPE<br>AWM<br><b>3 X 14AWG</b><br>600V, 24A<br>-40°C to +90°C<br>8.89mm OD   |                                          |                                                                  |                                                                                       |

\*\* Lengths in meters. Standard cable lengths are 1, 2, 5, 10 & 15 meters. Consult the factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling add -SS suffix. (e.g. PMIN-30MP-1M becomes PMIN-30MP-1M-SS)