



1 3/8" MIN Power Series Cordsets

4 & 5 Conductor MIN Power Series Cordsets, 10, 12 & 14AWG



Double Ended Cordsets | 600 Volt | IP67 Rating



5 pole is not UL listed.



Male Faceview	Cables	Straight Male to Straight Female	Right Angle Male to Right Angle Female	Right Angle Male to Straight Female	Straight Male to Right Angle Female
 1.375"-16UN2	Gray PVC STOOW 4 X 10 AWG 600V, 32A -40°C to +90°C 18mm OD	PMIN-40MFP-**-	PMIN-40MFP-**-R	PMIN-40MRFP-**-	PMIN-40MRFP-**-
	Gray PVC STOOW 4 X 14 AWG 600V, 20A -40°C to +90°C 14.7mm OD	PMIN-44MFP-**-	PMIN-44MFP-**-R	PMIN-44MRFP-**-	PMIN-44MRFP-**-
 1.375"-16UN2	Black TPE AWM 4 X 10 AWG 600V, 32A -40°C to +90°C 13.2 mm OD	PMINW-40MFP-**-C011	PMINW-40MFP-**-R-C011	PMINW-40MRFP-**-C011	PMINW-40MRFP-**-C011
	Black TPE AWM 4 X 12 AWG 600V, 25A -40°C to +90°C 10.9mm OD	PMINW-42MFP-**-C011	PMINW-42MFP-**-R-C011	PMINW-42MRFP-**-C011	PMINW-42MRFP-**-C011
	Black TPE AWM 4 X 14 AWG 600V, 20A -40°C to +90°C 9.7mm OD	PMINW-44MFP-**-C011	PMINW-44MFP-**-R-C011	PMINW-44MRFP-**-C011	PMINW-44MRFP-**-C011
 1.375"-16UN2	Black TPE AWM With Braided Shield 4 X 10 AWG 1 x 14 AWG (Drain) 600V, 25A -40°C to +90°C 13.1 mm OD	PMINWB-450MFP-**-C011	PMINWB-450MFP-**-R-C011	PMINWB-450MRFP-**-C011	PMINWB-450MRFP-**-C011

** Lengths in meters. Standard cable lengths are 1, 2, 5, 10 & 15 meters. Consult the factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling add -SS suffix. (e.g. PMIN-40MFP-1M becomes PMIN-40MFP-1M-SS)

Straight



Male Plug



Female Plug

Right Angle



Male Plug



Female Plug